



## **ASH FLOW**

The white structure and semi-transparent stain on this single-strip ash floor from the Lux Collection balances the light and dark contrasts in the wood, allowing the warm ash tones to softly filter through. Four-sided micro-bevelling at the edging ensures a classic full plank look and feel. Each board is carefully brushed to perfection to enhance the natural character of the grain. The light-absorbing, ultra-matt lacquer finish creates the impression of newly sawn timber, effectively eliminating glare while protecting the wood from daily wear.

	PRODUCT DETAILS	
Wood Flooring / 3-layer parquet	Hardness (Brinell) value /	4,0 / 2.
151N8AAKG4KW240 / 7393969045131	range	
1-strip / Ash	LRV / LRV Std1	55 / 6.8
Ultra matt lacquer / Stained	Warranty	30 year
	TECHNICAL DDODEDTIES	
Microbevelled 4-sided, Brushed		EN1318
187 x 2420 x 15 mm		LIVIDIO
22 kg / 8.15 kg	kg/m <sup>3</sup>	
	Reaction To Fire	EN1350
2.7 m² / 122.4 m²	Formaldehyde Emission	EN717-
	Content PCP	CEN/TR
,	Breaking Strength N/mm <sup>2</sup>	EN1533
Woodloc® 5S	— Thermal Resistance R-Value	
Floating, Glue-down	Biological Durability	EN350-
Yes		
Hardwood / 3.5 mm		CEN/TS
		CLIVITS
2-3 times	SHEEDIN COAST	
Pine/Spruce/Alder	The second	/ (
Spruce	~ 1AM 0.L.	es
	151N8AAKG4KW240 / 7393969045131 1-strip / Ash Ultra matt lacquer / Stained  Microbevelled 4-sided, Brushed 187 x 2420 x 15 mm 22 kg / 8.15 kg  2.7 m² / 122.4 m²  Lively Woodloc® 5S Floating, Glue-down Yes Hardwood / 3.5 mm  2-3 times Pine/Spruce/Alder	Wood Flooring / 3-layer parquet  151N8AAKG4KW240 / 7393969045131  1-strip / Ash  Ultra matt lacquer / Stained  Microbevelled 4-sided, Brushed  187 x 2420 x 15 mm  22 kg / 8.15 kg  2.7 m² / 122.4 m²  Lively  Woodloc® 5S  Floating, Glue-down Yes  Hardwood / 3.5 mm  Hardness (Brinell) value / range  LRV / LRV Std1  Warranty  TECHNICAL PROPERTIES Moisture content Minimun Mean Density kg/m³  Reaction To Fire Formaldehyde Emission Content PCP Breaking Strength N/mm² Thermal Resistance R-Value Biological Durability CARB2 Slip resistance

Hardness (Brinell) value /	4,0 / 2.8 - 6.2	
range		
LRV / LRV Std1	55 / 6.8	
Warranty	30 years	
TECHNICAL PROPERTIE	S	
Moisture content	EN13183	7%±2%
Minimun Mean Density		>500 kg/m <sup>3</sup>

kg/m <sup>3</sup>		_
Reaction To Fire	EN13501-1	Dfl-s1
Formaldehyde Emission	EN717-1	E1
Content PCP	CEN/TR14823	≤ 5 x 10-6n
Breaking Strength N/mm <sup>2</sup>	EN1533	NPD
Thermal Resistance R-Value		.11 (m2K/W)
Biological Durability	EN350-2	Class 1
CARB2		Compliant
Slip resistance	CEN/TS15676	NPD



## **DETAILED DESCRIPTION**

Naturally occurring wood colour variations allowed, from light to dark brown. The product includes large sound and black knots. Knots may vary in size and numbers.

Ultra matt lacquer: The appearance of the matte surface may vary due to different light sources and angles.

Colour change: Stained product - noticeable color change over time

Packages may contain start and stop boards.

## **Descriptions & Imagery**

## Other products in this collection

