



OAK NOUVEAU LACE

DDODLICT DETAIL C

The stain and soft contrast on this single-strip, white oak floor from the Classic Nouveau Collection results in an expression full of character. Each board is carefully brushed to bring out the character of the grain, knots and cracks and highlights the natural texture of the wood. Four-sided bevelling at the edges ensures a classic full plank look and feel. The matt lacquer finish eliminates glare while protecting the wood from daily wear.

| PRODUCT DETAILS | | PRODUCT DE |
|-----------------------------|---|-------------------|
| Product type / Construction | Wood Flooring / 3-layer parquet | Brinell value / r |
| Article Number / EAN Code | 151NAYEKS1KW240 / 7393969045117 | Warranty |
| Design / Wood Species | 1-strip / Oak | — TECHNICAL P |
| Surface treatment / | Matt lacquer / Stained | Moisture conte |
| Natural/Stained | | Minimun Mean |
| Design features | Brushed, Microbevelled 4-sided | — kg/m³ |
| Width x Length x Thickness | 187 x 2420 x 15 mm | Reaction To Fire |
| Weight per package / per | 22 kg / 8.15 kg | Formaldehyde |
| m2 | | |
| Area per package / per | 2.7 m ² / 122.4 m ² | Content PCP |
| pallet | | Breaking Streng |
| Grading | Lively | Thermal Condu |
| Joint | Woodloc® 5S | Thermal Resista |
| Installation method | Floating, Glue-down | Biological Dura |
| Floor heating | Yes | CARB2 |
| Wear leayer material / | Hardwood / 3.5 mm | Slip resistance |
| thickness | | TSCA |
| Resandable | 2-3 times | CARB P2 |
| Core material | Pine/Spruce/Alder | Compliant |
| Backside material | Spruce | floor |

PRODUCT DETAILS

| Brinell value / range | 3,7 / 2.2 - 5.9 | |
|----------------------------|-----------------|-------------|
| Warranty | 30 years | |
| TECHNICAL PROPERTIES | | |
| Moisture content | EN13183 | 7%±2% |
| Minimun Mean Density | | >500 kg/m³ |
| kg/m³ | | |
| Reaction To Fire | EN13501-1 | Dfl-s1 |
| Formaldehyde Emission | EN717-1 | E1 |
| Content PCP | CEN/TR14823 | ≤ 5 ppm |
| Breaking Strength N/mm² | EN1533 | NPD |
| Thermal Conductivity | EN12664 | 0,14 W/mK |
| Thermal Resistance R-Value | | .11 (m2K/W) |
| Biological Durability | EN350-2 | Class 1 |
| CARB2 | | Compliant |









CEN/TS15676





NPD







DETAILED DESCRIPTION

All naturally occuring wood colour variations allowed, from light to dark brown. Sapwood will occur. The product includes large sound and black knots, fillings and cracks. Knots, fillings and cracks will be present in all sizes and numbers.

Colour change: Stained product - noticeable color change over time.

Packages may contain start and stop boards.

Descriptions & Imagery

www.kahrs.com | ©Kährs

Other products in this collection



Oak Nouveau Whisper



Oak Nouveau Lace



Oak Nouveau Rich



Oak Nouveau Blonde



Oak Nouveau Gray



Oak Nouveau Tawny



Oak Nouveau Greige



Oak Nouveau White



Oak Nouveau Snow



Oak Nouveau Black