



## OAK NOUVEAU LACE

The stain and soft contrast on this single-strip, white oak floor from the Classic Nouveau Collection results in an expression full of character. Each board is carefully brushed to bring out the character of the grain, knots and cracks and highlights the natural texture of the wood. Four-sided bevelling at the edges ensures a classic full plank look and feel. The matt lacquer finish eliminates glare while protecting the wood from daily wear.

### PRODUCT DETAILS

<b>Article Number</b>	151NAYEKS1KW240
<b>EAN Code</b>	7393969045117
<b>Surface Treatment</b>	Matte finish
<b>Refining Treatment</b>	Brushed, Microbeveled 4-sided
<b>Dimensions</b>	7 3/8 x 95 1/4 "
<b>Weight per Package</b>	48.5 lbs
<b>Area per Package</b>	29.1 sqft
<b>Area per pallet</b>	1317.5 sqft
<b>Package info</b>	Packages may contain start and stop boards.

### DETAIL DESCRIPTION

All naturally occurring wood colour variations allowed, from light to dark brown. Sapwood will occur. The product includes large sound and black knots, fillings and cracks. Knots, fillings and cracks will be present in all sizes and numbers.

### COLOR CHANGE

Stained product - noticeable color change over time.


### FACTS

<b>Wood Species</b>	White Oak
<b>Design</b>	1-strip
<b>Grading</b>	Lively
<b>Range</b>	Kährs Original
<b>Collection</b>	Classic Nouveau Collection
<b>Resandable</b>	2 times
<b>Natural/Stained</b>	Stained
<b>Brinell Value</b>	3,7
<b>Joint</b>	Woodloc® 5S
<b>Floor heating</b>	Yes
<b>Warranty</b>	30 years
<b>Wear-layer material</b>	Hardwood
<b>Wear Layer Thickness</b>	1/8"
<b>Core material</b>	Pine/Spruce/Alder
<b>Backside material</b>	Spruce
<b>Thickness</b>	5/8"
<b>Installation method</b>	Floating, Glue-Down
<b>Surface Color</b>	White


### TECHNICAL PROPERTIES

<b>Moisture content</b>	EN13183	7%±2%
<b>Minimum Mean Density kg/m<sup>3</sup></b>	>500 kg/m <sup>3</sup>	
<b>Reaction To Fire</b>	EN13501-1	Dfl-s1
<b>Formaldehyde Emission</b>	EN717-1	E1
<b>Content PCP</b>	CEN/TR14823	≤ 5 x 10 <sup>-6</sup> n
<b>Breaking Strength N/mm<sup>2</sup></b>	EN1533	NPD
<b>Thermal Conductivity</b>	EN12664	0,14 W/mK
<b>Thermal Resistance R-Value</b>	.11 (m <sup>2</sup> K/W)	
<b>Biological Durability</b>	EN350-2	Class 1
<b>CARB2</b>	Compliant	
<b>Slip resistance</b>	CEN/TS15676	NPD

## Other products in this collection



Oak Nouveau Whisper



Oak Nouveau Lace



Oak Nouveau Blonde




Oak Nouveau Gray




Oak Nouveau Greige



Oak Nouveau White



Oak Nouveau Snow



Oak Nouveau Black

## CERTIFICATES



## Descriptions & Imagery

*All samples, images and product description, plus photo and brochure specifications are there for the sole purpose of giving an approximate idea of the items described in them. They shall not form part of the contract or have any contractual force and should be viewed for illustrative purposes only. We cannot guarantee that your computer's display or the quality of the print will accurately reflect the colour of the products. Your product may vary slightly from the images within this literature.*