



ASH STREAM

This single-strip, stained ash floor from the Lux Collection features earthy undertones and soft, stone grey hues. The pigmentation balances the light and dark contrasts in the wood and creates a dramatic impression. Four-sided micro-bevelling at the edging ensures a classic full plank look and feel. Each board is carefully brushed to perfection to enhance the natural character of the grain. The light-absorbing, ultra-matt lacquer finish creates the impression of newly sawn timber, effectively eliminating glare while protecting the wood from daily wear.

| PRODUCT DETAILS | | FACTS | | TECHNICAL PROPERTIES | | |
|--------------------|--|----------------------|---------------------|----------------------------|-------------|-----------|
| Article Number | 151N8AAKH4KW240 | Wood Species | Ash | Moisture content | EN13183 | 7%±2% |
| EAN Code | 7393969045223 | Design | 1-strip | Minimum Mean Density kg/m³ | >500 kg/m³ | |
| Surface treatment | Ultra matt lacquer The appearance of the matte surface may vary due to different light sources and angles. | Grading | Lively | | | |
| | | Range | Kährs Original | Reaction To Fire | EN13501-1 | Dfl-s1 |
| | | Collection | Lux Collection | Formaldehyde Emission | EN717-1 | E1 |
| Design features | Microbevelled 4-sided, Brushed | Resandable | 2-3 times | Content PCP | CEN/TR14823 | ≤ 5 ppm |
| Dimensions | 187 x 2420 mm | Natural/Stained | Stained | Breaking Strength N/mm² | EN1533 | NPD |
| Weight per Package | 22 kg | Brinell Value | 4,0 | Thermal Conductivity | EN12664 | 0,14 W/mK |
| Area per Package | 2.7 m² | Joint | Woodloc® 5S | Thermal Resistance R-Value | .11 (m2K/W) | |
| Area per pallet | 122.4 m² | Floor heating | Yes | Biological Durability | EN350-2 | Class 1 |
| Package info | Packages may contain start and stop boards. | Warranty | 30 years | CARB2 | Compliant | |
| DETAIL DESCRIPTION | Naturally occuring wood colour variations allowed, from light to dark brown. The product includes large sound and black knots. Knots may vary in size and numbers. | Wear-layer material | Hardwood | Slipperiness | CEN/TS15676 | NPD |
| | | Wear Layer Thickness | 3.5 mm | | | |
| | | Core material | Pine/Spruce/Alder | | | |
| | | Backside material | Spruce | | | |
| | | Thickness | 15 mm | | | |
| COLOUR CHANGE | | Installation method | Floating, Glue-down | | | |
| | | Surface Colour | Grey | | | |

Stained product - noticeable color change over time

Other products in this collection



Oak Crayon



Oak Biscotti



Oak Ghost



Oak Eggshell



Ash Stream



Ash Flow



Oak Sky



Oak Horizon



Oak Coast



Oak Shore



Oak Sun



Oak Terra

CERTIFICATES



Descriptions & Imagery

All samples, images and product description, plus photo and brochure specifications are there for the sole purpose of giving an approximate idea of the items described in them. They shall not form part of the contract or have any contractual force and should be viewed for illustrative purposes only. We cannot guarantee that your computer's display or the quality of the print will accurately reflect the colour of the products. Your product may vary slightly from the images within this literature.