



Living Collection



# OAK SHITAKE

Oak Shitake FSC with a micro bevelled edge is a clean even grade with few knots and a cool grey stain.

## PRODUCT DETAILS

|                                     |                               |
|-------------------------------------|-------------------------------|
| Product type / Construction         | Wood Flooring / Veneer floors |
| Article Number                      | 37101FEK1BFW 0                |
| Design / Wood Species               | Plank / White Oak             |
| Surface Treatment / Natural/Stained | Matte finish / Stained        |
| Refining Treatment                  | Microbeveled 4-sided, Brushed |
| Width x Length x Thickness          | 4 5/8 x 48 1/4 x 1/4"         |
| Weight per package / per m2         | 26.5 lbs / 15.6 lbs           |
| Area per package                    | 18.3 sqft                     |
| Grading                             | Variation                     |
| Joint                               | Woodloc®                      |
| Installation method                 | Floating, Glue-Down           |
| Floor heating                       | Yes                           |
| Wear leayer material / thickness    | Hardwood / 0"                 |
| Resandable                          | No                            |
| Core material                       | HDF                           |
| Backside material                   | Veneer                        |

## PRODUCT DETAILS

|                                  |               |
|----------------------------------|---------------|
| Hardness (Brinell) value / range | 5 - 6 / 5 - 6 |
|----------------------------------|---------------|

## TECHNICAL PROPERTIES

|                            |             |              |
|----------------------------|-------------|--------------|
| Moisture content           | EN13183     | 7%±2%        |
| Minimun Mean Density kg/m³ |             | >800 kg/m³   |
| Reaction To Fire           | EN13501-1   | Cfl-s1       |
| Formaldehyde Emission      | EN717-1     | E1           |
| Content PCP                | CEN/TR14823 | ≤ 5 x 10-6n  |
| Breaking Strength N/mm²    | EN1533      | NPD          |
| Thermal Conductivity       | EN12664     | 0,22 W/mK    |
| Thermal Resistance R-Value |             | .031 (m2K/W) |
| Biological Durability      | EN350-2     | Class 1      |
| CARB2                      |             | Compliant    |
| Slip resistance            | CEN/TS15676 | NPD          |



## DETAILED DESCRIPTION

Even colour with minor variations.  
Small sized knots in limited numbers allowed.

**Colour change:** Stained product - noticable color change over time.

Packages may contain start and stop boards.

## Descriptions & Imagery

All samples, images and product description, plus photo and brochure specifications are there for the sole purpose of giving an approximate idea of the items described in them. They shall not form part of the contract or have any contractual force and should be viewed for illustrative purposes only. We cannot guarantee that your computer's display or the quality of the print will accurately reflect the colour of the products. Your product may vary slightly from the images within this literature.

Kährs International |  
www.kährs.com | ©Kährs,  
USA & Canada 2026-04-11

