



## OAK SHELL

The powder white finish with soft contrast on this 3-strip oak floor from the Harmony Collection allows the warmer nuances to come through. The matt lacquer finish eliminates glare while protecting the wood from daily wear. Each board is carefully brushed to bring out the character of the grain and highlight the natural texture of the wood.

### PRODUCT DETAILS

|                                     |  |
|-------------------------------------|--|
| Product type / Construction         | Wood Floors / 3-layer parquet              |
| Article Number / EAN Code           | 153N6BEKS1KW240 / 7393969045124            |
| Design / Wood Species               | 3-strip / Oak                              |
| Surface treatment / Natural/Stained | Matt lacquer / Stained                     |
| Design features                     | Brushed                                    |
| Width x Length x Thickness          | 200 x 2421 x 15 mm                         |
| Weight per package / per m2         | 23 kg / 7.93 kg                            |
| Area per package / per pallet       | 2.91 m <sup>2</sup> / 130.1 m <sup>2</sup> |
| Grading                             | Lively                                     |
| Joint                               | Woodloc® 5S                                |
| Installation method                 | Floating, Glue-down                        |
| Floor heating                       | Yes  |
| Wear leayer material / thickness    | Hardwood / 3.5 mm                          |
| Resandable                          | 2-3 times                                  |
| Core material                       | Pine/Spruce/Alder                          |
| Backside material                   | Spruce                                     |

### PRODUCT DETAILS

|                                  |                 |
|----------------------------------|-----------------|
| Hardness (Brinell) value / range | 3,7 / 2.2 - 5.9 |
| Warranty                         | 30 years        |

### TECHNICAL PROPERTIES

|                                     |             |                        |
|-------------------------------------|-------------|------------------------|
| Moisture content                    | EN13183     | 7%±2%                  |
| Minimum Mean Density                |             | >500 kg/m <sup>3</sup> |
| Reaction To Fire                    | EN13501-1   | Dfl-s1                 |
| Formaldehyde Emission               | EN717-1     | E1                     |
| Content PCP                         | CEN/TR14823 | ≤ 5 ppm                |
| Breaking Strength N/mm <sup>2</sup> | EN1533      | NPD                    |
| Thermal Conductivity                | EN12664     | 0,11W/mK               |
| Biological Durability               | EN350-2     | Class 1                |
| CARB2                               |             | Compliant              |
| Slip resistance                     | CEN/TS15676 | NPD                    |



### DETAILED DESCRIPTION

Naturally occurring wood colour variations allowed, from light to dark brown. Sapwood will occur. The product includes medium sound and black knots. Knots may vary in size and numbers.

**Colour change:** Stained product - noticeable color change over time.

Packages may contain start and stop boards.

### Descriptions & Imagery

All samples, images and product description, plus photo and brochure specifications are there for the sole purpose of giving an approximate idea of the items described in them. They shall not form part of the contract or have any contractual force and should be viewed for illustrative purposes only. We cannot guarantee that your computer's display or the quality of the print will accurately reflect the colour of the products. Your product may vary slightly from the images within this literature.

www.kahrs.com | ©Kährs

2025-09-06

Other products in this collection



OAK SILK



OAK BROWNIE



OAK ALLOY



OAK PALE



OAK ALE



OAK CREME



OAK GRANITE



OAK LIMESTONE