



OAK VERONA

PRODUCT DETAILS

Construction	3-layer engineered
Article Number / EAN Code	152N38EK09KW240 / 7393969025171
Design / Wood Species	2-strip / White Oak
Surface Treatment / Natural/Stained	Matte finish / Natural
Width x Length x Thickness	7 7/8 x 95 3/8 x 5/8"
Weight per package / per m2	50.7 lbs / 17.4 lbs
Area per package / per pallet	31.3 sqft / 1409.5 sqft
Grading	Variation
Joint	Woodloc® 5S
Installation method	Glue-Down, Floating
Floor heating	Yes
Wear leayer material / thickness	Hardwood / 1/8"
Resandable	2 times
Core material	Pine/Spruce/Alder
Brinell value / range	3,7 / 2.2 - 5.9
LRV / LRV Std1	28 / 3.3

TECHNICAL PROPERTIES

Moisture content	EN13183	7%±2%
Minimun Mean Density kg/m ³		>500 kg/m ³
Reaction To Fire	EN13501-1	Dfl-s1
Formaldehyde Emission	EN717-1	E1
Content PCP	CEN/TR14823	≤ 5 x 10-6n
Breaking Strength N/mm ²	EN1533	NPD
Thermal Conductivity	EN12664	0,14 W/mK
Thermal Resistance R-Value		.11 (m2K/W)
Biological Durability	EN350-2	Class 1
CARB2		Compliant
Slip resistance	CEN/TS15676	NPD



DETAILED DESCRIPTION

Naturally occuring wood colour variations allowed, from light to dark brown. Sapwood may occur. The product includes medium sound and black knots. Knots may vary in size and numbers.

Colour change: Some muting of colour variation to medium, straw brown.

Packages may contain start and stop boards.

Descriptions & Imagery

All samples, images and product description, plus photo and brochure specifications are there for the sole purpose of giving an approximate idea of the items described in them. They shall not form part of the contract or have any contractual force and should be viewed for illustrative purposes only. We cannot guarantee that your computer's display or the quality of the print will accurately reflect the colour of the products. Your product may vary slightly from the images within this literature.

Kährs International |
www.kährs.com | ©Kährs,
USA & Canada 2024-07-27

Other products in this collection



Oak Verona



Oak Siena