



# OAK MAISON

The combination of smoking and white oil gives this single-strip oak floor from the Grande Collection a dusky blue finish with pale ashen highlights in the pores. The colour variation between boards is very apparent due to the fully smoked planks. Every board is carefully brushed to bring out the character of the grain and highlight the natural texture of the wood. Four-sided bevelling at the edges ensures a classic, full plank look and feel. Each board is meticulously hand-scraped, which enhances the rustic appearance of the floor. This product must be oiled after installation and prior to use.

PRODUCT DETAILS		TECHNICAL PROPERTIES		
Product type / Construction	Wood Floors / 3-layer parquet	Moisture content	EN13183	7%±2%
Article Number / EAN Code	201XABEKFBE280 / 7393969031509	Minimum Mean Density	>500 kg/m <sup>3</sup>	
Design / Wood Species	1-strip / Oak	kg/m <sup>3</sup>		
Surface treatment / Natural/Stained	Oil / Stained	Reaction To Fire	EN13501-1	Dfl-s1
Design features	Brushed, Smoked, Handscraped, Bevelled 4-sided	Formaldehyde Emission	EN717-1	E1
Width x Length x Thickness	260 x 2800 x 20 mm	Content PCP	CEN/TR14823	≤ 5 ppm
Weight per package / per m <sup>2</sup>	38 kg / 13.1 kg	Breaking Strength N/mm <sup>2</sup>	EN1533	NPD
Area per package	2.9 m <sup>2</sup>	Thermal Conductivity	EN12664	0,125 W/mK
Grading	Variation	Thermal Resistance R-Value	.16 (m <sup>2</sup> K/W)	
Joint	Tongue & Groove	Biological Durability	EN350-2	Class 1
Installation method	Glue-down	CARB2	Compliant	
Floor heating	No	Slip resistance	CEN/TS15676	NPD
Wear layer material / thickness	Hardwood / 5 mm			
Resandable	2-4 times			
Backside material	Veneer			
Warranty	30 years			



## DETAILED DESCRIPTION

Naturally occurring wood colour variations allowed, from light to dark brown. The smoked design is likely to enhance the naturally occurring wood color variations and create further contrast between light and dark. The product includes large sound and black knots. Knots may vary in size and numbers. Grande products may continue to develop their rustic nature after the floor has been installed; splits and cracks that occur after installation are normal and should be considered part of the timbers natural character.

- Oil:** This floor should be oiled immediately after installation.
- Colour change:** Smoked product - noticeable color change over time.
- Packages may contain start and stop boards.

