



## OAK COMO

PRODUCT DETAILS

Oak Como is a floor with strips selected to provide a calm appearance but still with certain degree of variation in the grain.

roduct type / Construction Wood Floors / 3-layer parquet	
153N38EK50GW 0 / 7393969030236	i
3-strip / Oak	
Satin lacquer / Natural	
	Ī
200 x 2423 x 15 mm	(
23 kg / 7.93 kg	i
	-
2.9 m <sup>2</sup>	-
Variation	i
Woodloc® 5S	(
Floating, Glue-down	
Yes	
Hardwood / 3.5 mm	
2-3 times	
Pine/Spruce lamella	
3,7 / 2.2 - 5.9	
30 years	
	153N38EK50GW 0 / 7393969030236 3-strip / Oak Satin lacquer / Natural  200 x 2423 x 15 mm 23 kg / 7.93 kg  2.9 m² Variation Woodloc® 5S Floating, Glue-down Yes Hardwood / 3.5 mm  2-3 times Pine/Spruce lamella 3,7 / 2.2 - 5.9

TECHNICAL	PROPERTIES

Moisture content	EN13183	7%±2%
Minimun Mean Density		>500 kg/m³
kg/m³		
Reaction To Fire	EN13501-1	Dfl-s1
Formaldehyde Emission	EN717-1	E1
Content PCP	CEN/TR14823	≤ 5 ppm
Breaking Strength N/mm <sup>2</sup>	EN1533	NPD
Thermal Conductivity	EN12664	0,11W/mK
Thermal Resistance R-Value		.11 (m2K/W)
Biological Durability	EN350-2	Class 1
CARB2		Compliant
Slip resistance	CEN/TS15676	NPD



















## DETAILED DESCRIPTION

Naturally occuring wood colour variations allowed, from light to dark brown.

The product includes medium sound and black knots. Knots may vary in size and numbers.

Colour change: Some muting of colour variation to medium, straw brown.

Packages may contain start and stop boards.

## Other products in this collection

