

JATOBA BRASILIA

Jatoba Brasilia is a dark, somewhat reddish floor.

PRODUCT DETAILS		TECHNICAL PROPERTIES		
Product type / Construction	Wood Floors / 3-layer parquet	Moisture content	EN13183	7%±2%
Article Number / EAN Code	152N54JO50KW 0 / 7393969023917	Minimun Mean Density		>500 kg/m³
Design / Wood Species	2-strip / Jatoba	kg/m³		
Surface treatment /	Satin lacquer / Natural	Reaction To Fire	EN13501-1	Dfl-s1
Natural/Stained		Formaldehyde Emission	EN717-1	E1
Width x Length x Thickness	200 x 2423 x 15 mm	Content PCP	CEN/TR14823	≤ 5 ppm
Weight per package / per	27.5 kg / 9.48 kg	Breaking Strength N/mm ²	EN1533	NPD
m2		Thermal Conductivity	EN12664	0,11W/mK
Area per package	2.9 m ²	Thermal Resistance R-Value		.11 (m2K/W)
Grading	Calm	Biological Durability	EN350-2	Class 1
Joint	Woodloc® 5S	CARB2		Compliant
Installation method	Glue-down, Floating	Slip resistance	CEN/TS15676	NPD
Floor heating	Yes			
Wear leayer material /	Hardwood / 3.5 mm			
thickness		CARB P2 Compliant SundaHus	BASTA	
Resandable	2-3 times			
Core material	Pine/Spruce lamella			
Hardness (Brinell) value /	7,0 / 4.5 - 14.1			
range				
Warranty	30 years			

DETAILED DESCRIPTION

Naturally occuring wood colour variations allowed, from light to dark red.

Small sized knots in limited numbers allowed.

Colour change: Pronounced deepening and darkening of colors. Yellowish and white spot may occur.

Packages may contain start and stop boards.

Descriptions & Imagery

All samples, images and product description, plus photo and brochure specifications are there for the sole purpose of giving an approximate idea of the items described in them. They shall not form part of the contract or have any contractual force and should be viewed for illustrative purposes only. We cannot guarantee that your computer's display or the quality of the print will accurately reflect the colour of the products. Your product may vary slightly from the images within this literature.

www.kahrs.com | [©]Kährs {year}