



## PARK OAK

Park Oak is a rustic one strip design. May contain knots, sap wood and colour variation.

| PRODUCT DETAILS   |   | FACTS                |                     | TECHNICAL PROPERTIES                  |             |               |
|---|---|----------------------|---------------------|---------------------------------------|-------------|---------------|
| Article Number  | 101P6AEK09KW120                             | Wood Species         | Oak                 | Moisture                              | EN13183     | 7%±2%         |
| EAN Code  | 7393969030595                               | Design               | 1-strip             | content                               |             |               |
| Surface Treatment                                       | Matt lacquer                                | Grading              | Lively              | Minimun Mean Density kg/m³ >800 kg/m³ |             |               |
| Refining Treatment                                      | Bevelled 4-sided,<br>Brushed                | Range                | Kährs Spirit        | Reaction To<br>Fire                   | EN13501-1   | Cfl-s1        |
|   |   | Collection           | Unity Collection    | Formaldehyde<br>Emission              | EN717-1     | E1            |
| Dimensions  | 125 x 1200 mm                               | Natural/Stained      | Natural             |                                       |             |               |
| Weight per Package                                      | 14 kg                                       | loint                | Woodloc®            | Content PCP                           | CEN/TR1482  | 3 ≤ 5 x 10-6n |
| Area per Package  | 1.5 m <sup>2</sup>                          | Floor heating        | Yes                 | Breaking                              | EN1533      | NPD           |
| Package info  | Packages may contain start and stop boards. | Wear-layer material  | Hardwood            | Strength N/mm <sup>2</sup>            |             |               |
|   |   | Wear Layer Thickness | 1.9 mm              | Thermal                               | EN12664     | 0,14 W/mK     |
| COLOUR CHANGE   |   | Core material        | HDF                 | Conductivity                          |             |               |
| Some muting of colour variation to medium, straw brown. |   | Backside material    | Veneer              | Thermal Resistance R-Value            |             | .07 (m2K/W)   |
|   |   |                      | 10 mm               | Biological<br>Durability              | EN350-2     | Class 1       |
|   |   | Installation method  | Floating, Glue-down | CARB2                                 |             | Compliant     |
|   |   |                      |                     | Slipperiness                          | CEN/TS15676 | 5 NPD         |

## Other products in this collection









Reef Oak

Park Oak

**Orchard Walnut** 

Garden Walnut



Arctic Oak

## CERTIFICATES







## **Descriptions & Imagery**

All samples, images and product description, plus photo and brochure specifications are there for the sole purpose of giving an approximate idea of the items described in them. They shall not form part of the contract or have any contractual force and should be viewed for illustrative purposes only. We cannot guarantee that your computer's display or the quality of the print will accurately reflect the colour of the products. Your product may vary slightly from the images within this literature.