



## ASH FALSTERBO

This 2-strip ash floor from the Sand Collection features a clean, white finish that enhances the natural grain of the timber. The matt lacquer finish eliminates glare while protecting the wood from daily wear.

| PRODUCT DETAILS   |   | FACTS                |                     | TECHNICAL PROPERTIES                        |                |                        |
|---|---|----------------------|---------------------|---|----------------|------------------------|
| Article Number  | 152N55AK0VKW240                             | Wood Species         | Ash                 | Moisture                                    | EN13183        | 7%±2%                  |
| EAN Code  | 7393969028226                               | Design               | 2-strip             | content                                     |                |                        |
| Surface treatment   | Matt lacquer                                | Grading              | Calm                | Minimun Mean Density kg/m³ >500 kg          |                | >500 kg/m <sup>3</sup> |
| Dimensions  | 200 x 2423 mm                               | Range                | Kährs Original      | Reaction To<br>Fire                         | EN13501-1      | Dfl-s1                 |
| Weight per Package  | 23 kg                                       | Collection           | Sand Collection     | Formaldehyde<br>Emission                    | EN717-1        | E1                     |
| Area per Package  | 2.91 m <sup>2</sup>                         | Resandable           | 2-3 times           |   |                |                        |
| Area per pallet   | 130.95 m²                                   | Natural/Stained      | Stained             | Content PCP                                 | CEN/TR14823    | ≤ 5 ppm                |
| Package info  | Packages may contain start and stop boards. | Brinell Value        | 4,0                 | Breaking                                    | EN1533         | NPD                    |
|   |   | Joint                | Woodloc® 5S         | <ul> <li>Strength</li> <li>N/mm²</li> </ul> |                |                        |
| DETAIL DESCRIPTION  |   | Floor heating        | Yes                 | Thermal                                     | EN12664        | 0,14 W/mK              |
| Even light colour with minor variations. Small sized knots in limited numbers allowed.  COLOUR CHANGE |   | Warranty             | 30 years            | Conductivity                                |                |                        |
|   |   | Wear-layer material  | Hardwood            | Thermal Resistance R-Value                  |                | .11 (m2K/W)            |
|   |   | Wear Layer Thickness | 3.5 mm              | Biological<br>Durability                    | EN350-2        | Class 1                |
| Stained product - noticable color change over time.   |   | Core material        | Pine/Spruce/Alder   | CARB2                                       |                | Compliant              |
|   |   | Thickness            | 15 mm               | Slipperiness                                | CEN/TS15676    |                        |
|   |   | Installation method  | Floating, Glue-down | supportiness                                | CL. 17 1313070 |                        |
|   |   | Surface Colour       | White A0V           |   |                |                        |

## Other products in this collection



Oak Amalfi



Oak Rügen



Oak Norderney



Oak Estoril



Oak Sorrento



Oak Portofino



Oak Brighton



Ash Skagen



Ash Sandvig



Ash Falsterbo

## **CERTIFICATES**





















## **Descriptions & Imagery**

All samples, images and product description, plus photo and brochure specifications are there for the sole purpose of giving an approximate idea of the items described in them. They shall not form part of the contract or have any contractual force and should be viewed for illustrative purposes only. We cannot guarantee that your computer's display or the quality of the print will accurately reflect the colour of the products. Your product may vary slightly from the images within this literature.