

## ASH KALMAR SATIN

The blonde hues found in this 3-strip ash floor from the Nordic Naturals Collection range from amber honey to vanilla cream. To create this lively effect, lighter surface wood has been mixed with darker core wood.

	PRODUCT DETAILS		
Wood Floors / 3-layer parquet	Warranty	30 years	
153N18AK50KW240 / 7393969020534	TECHNICAL PROPERTIES		
3-strip / Ash			7%±2%
Satin lacquer / Natural		ENTOTOS	>500 kg/m <sup>3</sup>
	5		500 Kg/m
200 x 2423 x 15 mm		EN13501-1	Dfl-s1
23 kg / 7.93 kg	Formaldehyde Emission	EN717-1	E1
	Content PCP	CEN/TR14823	≤ 5 ppm
2.9 m² / 130.1 m²	Breaking Strength N/mm <sup>2</sup>	EN1533	NPD
		EN12664	0,11W/mK
Variation			.11 (m2K/W)
Woodloc® 5S			Class 1
Floating, Glue-down		2113302	Compliant
Yes	-	CEN/TS15676	NPD
Hardwood / 3.5 mm		CLIV/1315070	INF D
		ethistion care	Emissions own cuit entiteture
2-3 times	CARB P2		
Pine/Spruce lamella	Compliant Sundality		
4,0 / 2.8 - 6.2	floor CC		
43 / 9.8	-		
	153N18AK50KW240 / 7393969020534 3-strip / Ash Satin lacquer / Natural 200 x 2423 x 15 mm 23 kg / 7.93 kg 2.9 m <sup>2</sup> / 130.1 m <sup>2</sup> Variation Woodloc® 5S Floating, Glue-down Yes Hardwood / 3.5 mm 2-3 times Pine/Spruce lamella 4,0 / 2.8 - 6.2	Wood Floors / 3-layer parquetWarranty153N18AK50KW240 / 7393969020534TECHNICAL PROPERTIES3-strip / AshMoisture contentSatin lacquer / NaturalMinimun Mean Density200 x 2423 x 15 mmReaction To Fire23 kg / 7.93 kgFormaldehyde Emission2.9 m² / 130.1 m²Content PCP2.9 m² / 130.1 m²Breaking Strength N/mm²VariationContent PCPVodloc® 5SBiological DurabilityFloating, Glue-downCARB2YesSlip resistanceHardwood / 3.5 mmSlip resistance2-3 timesSlip resistancePine/Spruce lamella4,0 / 2.8 - 6.2	Wood Floors / 3-layer parquetWarranty30 years153N18AK50KW240 / 7393969020534TECHNICAL PROPERTIES3-strip / AshMoisture contentEN13183Satin lacquer / NaturalMinimun Mean Density200 x 2423 x 15 mmReaction To FireEN13501-123 kg / 7.93 kgFormaldehyde EmissionEN717-12.9 m² / 130.1 m²Content PCPCEN/TR148232.9 m² / 130.1 m²Breaking Strength N/mm²EN1533VariationThermal Resistance R-ValueBiological DurabilityEN350-2Voodloc® 5SBiological DurabilityEN350-2Floating, Glue-downCARB2Sip resistanceCEN/TS15676YesSip resistanceCEN/TS15676CEN/TS15676Hardwood / 3.5 mmITSCAImage With Strange With S

## DETAILED DESCRIPTION

Naturally occuring wood colour variations allowed, from light to dark brown.

The product includes medium sound and black knots. Knots may vary in size and numbers.

Colour change: Pale cream darkens to straw tan.

Packages may contain start and stop boards.

## Descriptions & Imagery

www.kahrs.com | <sup>©</sup>Kährs 2025-05-09

All samples, images and product description, plus photo and brochure specifications are there for the sole purpose of giving an approximate idea of the items described in them. They shall not form part of the contract or have any contractual force and should be viewed for illustrative purposes only. We cannot guarantee that your computer's display or the quality of the print will accurately reflect the colour of the products. Your product may vary slightly from the images within this literature.

## Other products in this collection



BEECH VIBORG



ASH KALMAR MATT



ASH GOTLAND