



ASH KALMAR SATIN

European Ash, three strip, silk matte finish. Lively rustic look, some knots.

PRODUCT DETAILS

Product type / Construction	Wood Flooring / 3-layer engineered
Article Number / EAN Code	153N18AK50KW240 / 7393969020534
Design / Wood Species	3-strip / Ash
Surface Treatment / Natural/Stained	Silk matte finish / Natural
Width x Length x Thickness	7 7/8 x 95 3/8 x 5/8"
Weight per package / per m2	50.7 lbs / 17.5 lbs
Area per package / per pallet	31.3 sqft / 1400.4 sqft
Grading	Variation
Joint	Woodloc® 5S
Installation method	Floating, Glue-Down
Floor heating	Yes
Wear layer material / thickness	Hardwood / 1/8"
Resandable	2 times
Core material	Pine/Spruce
Hardness (Brinell) value / range	4,0 / 2.8 - 6.2
LRV / LRV Std1	43 / 9.8

TECHNICAL PROPERTIES

Moisture content	EN13183	7%±2%
Minimum Mean Density		>500 kg/m ³
Reaction To Fire	EN13501-1	Dfl-s1
Formaldehyde Emission	EN717-1	E1
Content PCP	CEN/TR14823	≤ 5 x 10-6n
Breaking Strength N/mm ²	EN1533	NPD
Biological Durability	EN350-2	Class 1
CARB2		Compliant
Slip resistance	CEN/TS15676	NPD



DETAILED DESCRIPTION

Naturally occurring wood colour variations allowed, from light to dark brown.
The product includes medium sound and black knots. Knots may vary in size and numbers.

Colour change: Pale cream darkens to straw tan.

Packages may contain start and stop boards.

Descriptions & Imagery

All samples, images and product description, plus photo and brochure specifications are there for the sole purpose of giving an approximate idea of the items described in them. They shall not form part of the contract or have any contractual force and should be viewed for illustrative purposes only. We cannot guarantee that your computer's display or the quality of the print will accurately reflect the colour of the products. Your product may vary slightly from the images within this literature.

Kährs International |
www.kahrs.com | ©Kährs,
USA & Canada 2025-08-31

Other products in this collection



Beech Viborg



Ash Gotland