



ASH KALMAR SATIN

European Ash, three strip, silk matte finish. Lively rustic look, some knots.

PRODUCT DETAILS Product type / Construction Wood Flooring / 3-layer engineered Article Number / EAN Code 153N18AK50KW240 / 7393969020534 Design / Wood Species 3-strip / Ash Silk matte finish / Natural Surface Treatment / Natural/Stained Width x Length x Thickness 7 7/8 x 95 3/8 x 5/8" 50.7 lbs / 17.5 lbs Weight per package / per m2 31.2 sqft / 1400.4 sqft Area per package / per pallet Grading Variation Joint Woodloc® 5S Installation method Floating, Glue-Down Floor heating Wear leayer material / Hardwood / 1/8" thickness Resandable 2 times Core material Pine/Spruce lamella Hardness (Brinell) value / 4,0 / 2.8 - 6.2 range

TECHNICAL PROPERTIES

Moisture content	EN13183	7%±2%
Minimun Mean Density		>500 kg/m³
kg/m³		
Reaction To Fire	EN13501-1	Dfl-s1
Formaldehyde Emission	EN717-1	E1
Content PCP	CEN/TR14823	≤ 5 x 10-6n
Breaking Strength N/mm ²	EN1533	NPD
Thermal Resistance R-Value		.11 (m2K/W)
Biological Durability	EN350-2	Class 1
CARB2		Compliant
Slip resistance	CEN/TS15676	NPD











DETAILED DESCRIPTION

LRV / LRV Std1

Naturally occuring wood colour variations allowed, from light to dark brown.

43 / 9.8

The product includes medium sound and black knots. Knots may vary in size and numbers.

Colour change: Pale cream darkens to straw tan.

Packages may contain start and stop boards.

Other products in this collection





Beech Viborg

Ash Gotland