



## OAK COMO

Oak Como is a floor with strips selected to provide a calm appearance but still with certain degree of variation in the grain.

PRODUCT DETAILS	
Product type / Construction	Wood Floors / 3-layer parquet
Article Number / EAN Code	153N38EK09GW240 / 7393969031103
Design / Wood Species	3-strip / Oak
Surface treatment /	Matt lacquer / Natural
Natural/Stained	
Width x Length x Thickness	200 x 2423 x 15 mm
Weight per package / per	23 kg / 7.93 kg
m2	
Area per package / per	2.91 m <sup>2</sup> / 130.95 m <sup>2</sup>
pallet	
Grading	Variation
Joint	Woodloc® 5S
Installation method	Floating, Glue-down
Floor heating	Yes
Wear leayer material /	Hardwood / 3.5 mm
thickness	
Resandable	2-3 times
Core material	Pine/Spruce
Hardness (Brinell) value /	3,7 / 2.2 - 5.9
range	

Ρ	RO	DU	ICT	DE.	ΓΑΙ	LS

Warranty	30 years	
TECHNICAL PROPERTIES	5	
Moisture content	EN13183	7%±2%
Minimun Mean Density		>500 kg/m³
kg/m³		
Reaction To Fire	EN13501-1	Dfl-s1
Formaldehyde Emission	EN717-1	E1
Content PCP	CEN/TR14823	≤ 5 ppm
Breaking Strength N/mm <sup>2</sup>	EN1533	NPD
Thermal Conductivity	EN12664	0,11W/mK
Biological Durability	EN350-2	Class 1
CARB2		Compliant
Slip resistance	CEN/TS15676	NPD



















## **DETAILED DESCRIPTION**

Naturally occuring wood colour variations allowed, from light to dark brown.

The product includes medium sound and black knots. Knots may vary in size and numbers.

**Colour change**: Some muting of colour variation to medium, straw brown.

Packages may contain start and stop boards.

## Other products in this collection

