



# CHERRY SAVANNAH

The warm rosy hues found in this 3-strip cherry floor from the American Naturals Collection are perfectly balanced, resulting in a subtle and harmonious expression. The silk lacquer finish gives the floor a polished appearance and brings out the natural character of the timber. The even finish protects the wood from daily wear, without adding artificial shine.

## PRODUCT DETAILS

|                    |   |
|--------------------|---|
| Article Number     | 153N15CH50KW240                             |
| EAN Code           | 7393969018852                               |
| Surface treatment  | Silk lacquer                                |
| Dimensions         | 200 x 2423 mm                               |
| Weight per Package | 23 kg                                       |
| Area per Package   | 2.9 m <sup>2</sup>                          |
| Package info       | Packages may contain start and stop boards. |

## DETAIL DESCRIPTION

Even colour with minor variations. Small sized knots in limited numbers allowed.

## COLOUR CHANGE

Changes from pink hues to deeper reddish brown tones.

## FACTS

|                      |                              |
|----------------------|------------------------------|
| Wood Species         | Cherry                       |
| Design               | 3-strip                      |
| Grading              | Calm                         |
| Range                | Kährs Original               |
| Collection           | American Naturals Collection |
| Resandable           | 2-3 times                    |
| Natural/Stained      | Natural                      |
| Brinell Value        | 3,6                          |
| Joint                | Woodloc® 5S                  |
| Floor heating        | Yes                          |
| Warranty             | 30 years                     |
| Warranty US          | 25 years                     |
| Wear-layer material  | Hardwood                     |
| Wear Layer Thickness | 3.5 mm                       |
| Core material        | Pine/Spruce lamella          |
| Thickness            | 15 mm                        |
| Installation method  | Glue-down, Floating          |

## TECHNICAL PROPERTIES

|  |                        |           |
|--|------------------------|-----------|
| Moisture content                       | EN13183                | 7%±2%     |
| Minimum Mean Density kg/m <sup>3</sup> | >500 kg/m <sup>3</sup> |           |
| Reaction To Fire                       | EN13501-1              | Dfl-s1    |
| Formaldehyde Emission                  | EN717-1                | E1        |
| Content PCP                            | CEN/TR14823            | ≤ 5 ppm   |
| Breaking Strength N/mm <sup>2</sup>    | EN1533                 | NPD       |
| Thermal Conductivity                   | EN12664                | 0,14 W/mK |
| Thermal Resistance R-Value             | .11 (m2K/W)            |           |
| Biological Durability                  | EN350-2                | Class 1   |
| CARB2                                  | Compliant              |           |
| Slipperiness                           | CEN/TS15676            | NPD       |

Other products in this collection



Walnut Georgia



Walnut Montreal



Walnut Hartford



Hard Maple Toronto



Cherry Savannah

CERTIFICATES



Descriptions & Imagery

All samples, images and product description, plus photo and brochure specifications are there for the sole purpose of giving an approximate idea of the items described in them. They shall not form part of the contract or have any contractual force and should be viewed for illustrative purposes only. We cannot guarantee that your computer's display or the quality of the print will accurately reflect the colour of the products. Your product may vary slightly from the images within this literature.