



JARRAH SYDNEY

Three strip design, silk matte finish, color variation.

PRODUCT DETAILS

Product type / Construction	Wood Flooring / 3-layer engineered
Article Number / EAN Code	153N15JH50KW 0 / 7393969015875
Design / Wood Species	3-strip / Jarrah
Surface Treatment / Natural/Stained	Satin finish / Natural
Width x Length x Thickness	7 7/8 x 95 3/8 x 5/8"
Weight per package / per m2	50.7 lbs / 17.5 lbs
Area per package / per pallet	31.2 sqft / 1400.4 sqft
Grading	Calm
Joint	Woodloc® 5S
Installation method	Floating, Glue-Down
Floor heating	Yes
Wear leayer material / thickness	Hardwood / 1/8"
Resandable	2 times
Core material	Pine/Spruce
Hardness (Brinell) value / range	4,7 / 2.9 - 9.0
Warranty	25 years

TECHNICAL PROPERTIES

Moisture content	EN13183	7%±2%
Minimun Mean Density		>500 kg/m ³
Reaction To Fire	EN13501-1	Dfl-s1
Formaldehyde Emission	EN717-1	E1
Content PCP	CEN/TR14823	≤ 5 x 10-6n
Breaking Strength N/mm ²	EN1533	NPD
Biological Durability	EN350-2	Class 1
CARB2		Compliant
Slip resistance	CEN/TS15676	NPD



DETAILED DESCRIPTION

Naturally occuring wood colour variations allowed, from light to dark red.

Small sized knots in limited numbers allowed.

Colour change: Darkening towards deeper red/red browns.

Packages may contain start and stop boards.

Descriptions & Imagery

All samples, images and product description, plus photo and brochure specifications are there for the sole purpose of giving an approximate idea of the items described in them. They shall not form part of the contract or have any contractual force and should be viewed for illustrative purposes only. We cannot guarantee that your computer's display or the quality of the print will accurately reflect the colour of the products. Your product may vary slightly from the images within this literature.

Kährs International |
www.kährs.com | ©Kährs,
USA & Canada 2026-04-11

