



## ARCTIC OAK

One strip design, matte finish, slight color variation, brushed, four sided bevel, may contain some knots. Features Kährs ECO Core.

PRODUCT DETAILS		FACTS		TECHNICAL PROPERTIES		
Article Number	101P6AEK0DKW120	Wood Species	White Oak	Moisture	EN13183	7%±2%
EAN Code	7393969030656	Design	1-strip	content		
Surface Treatment	Matte finish	Grading	Variation	Minimun Mean Density kg/m³ >800 kg/m³		
Refining Treatment	Beveled 4-sided, Brushed	Range	Kährs Spirit	Reaction To Fire	EN13501-1	Cfl-s1
Dimensions	4 7/8 x 47 1/4 "	Collection	Unity Collection	Formaldehyde Emission	EN717-1	E1
Weight per Package	30.9 lbs	Resandable	1 time			
Area per Package	16.1 sqft	Natural/Stained	Stained	Content PCP	CEN/TR14823	≤ 5 x 10-6n
Package info	Packages may contain start and stop boards.	Joint	Woodloc®	Breaking Strength N/mm²	EN1533	NPD
		Floor heating	Yes			
DETAIL DESCRIPTION		Warranty	20 years	Thermal Conductivity	EN12664	0,14 W/mK
from light to dark brown. The product includes large sound and black knots and cracks. Knots and cracks may vary in size and numbers.  Color Change		Warranty	20 years			
		Wear-layer material	Hardwood	Thermal Resistance R-Value		.07 (m2K/W)
		Wear Layer Thickness	1/8"	Biological Durability	EN350-2	Class 1
		Core material	HDF	CARB2		Compliant
		Thickness	3/8"		CEN/TS15676	
Stained product - noticable color change over time.		Installation method	Floating, Glue-Down		CLIW/13130/0	INF D
		Surface Color	White			

## **CERTIFICATES**







## **Descriptions & Imagery**

All samples, images and product description, plus photo and brochure specifications are there for the sole purpose of giving an approximate idea of the items described in them. They shall not form part of the contract or have any contractual force and should be viewed for illustrative purposes only. We cannot guarantee that your computer's display or the quality of the print will accurately reflect the colour of the products. Your product may vary slightly from the images within this literature.