



Class 1 Compliant

NPD

## CASA OAK

A rustic, handscraped product that contains knots and cracks. This product must be oiled after installation and prior to use.

PRODUCT DETAILS		TECHNICAL PROPERTIES
Product type / Construction	Wood Flooring / 3-layer engineered	Moisture content
Article Number / EAN Code	201XCDEKF0KE280 / 7393969031578	Minimun Mean Density
Design / Wood Species	1-strip / White Oak	kg/m³
Surface Treatment /	Oil / Natural	Reaction To Fire
Natural/Stained		Formaldehyde Emission
Refining Treatment	Beveled 4-sided, Handscraped	Content PCP
Width x Length x Thickness	10 1/4 x 110 1/4 x 3/4"	Breaking Strength N/mm²
Weight per package / per	83.8 lbs / 28.9 lbs	Thermal Conductivity
m2		Thermal Resistance R-Value
Area per package / per	31.3 sqft / 877 sqft	Biological Durability
pallet		CARB2
Grading	Dynamic	Slip resistance
Joint	Tongue & Groove	(2)
Installation method	Glue-Down	TSCA TITLE VI CARB P2 Compliant
Floor heating	No	
Wear leayer material /	Hardwood / 1/4"	
thickness		
Resandable	2 times	

Moisture content	EN13183	7%±2%
Minimun Mean Density		>500 kg/m³
kg/m³		
Reaction To Fire	EN13501-1	Dfl-s1
Formaldehyde Emission	EN717-1	E1
Content PCP	CEN/TR14823	≤ 5 x 10-6n
Breaking Strength N/mm²	EN1533	NPD
Thermal Conductivity	EN12664	0,125 W/mK
Thermal Resistance R-Value	.16 (m2K/W)	

EN350-2

CEN/TS15676



## **TECHNICAL PROPERTIES**

## DETAILED DESCRIPTION

Backside material

Naturally occuring wood color variations allowed, from light to dark brown. The product includes large sound and black knots. Knots may vary in size and numbers. Grande products may continue to develop their rustic nature after the floor has been installed; splits and cracks that occur after installation are normal and should be considered part of the timbers natural character.

Oil: This floor should be oiled immediately after installation.

Colour change: Stained product - noticable color change over time.

Veneer

Packages may contain start and stop boards.

