



OAK CHILLON

The grey stain on this single-strip oak floor from the Royal Collection allows the nuances in the wood to seep through, resulting in a balanced expression. Each board is carefully brushed to bring out the character of the grain and highlight the natural texture of the wood. Four-sided bevelling at the edges ensures a classic, full plank look and feel.

PRODUCT DETAILS		FACTS		TECHNICAL PROPERTIES		
Article Number	181XADEK32KW240	Wood Species	Oak	Moisture	EN13183	7%±2%
EAN Code	7393969047074	Design	1-strip	content		
Surface treatment	Oil This floor should be oiled immediately after installation.	Grading	Dynamic	Minimun Mean Density kg/m³ >500 kg/m³		
		Range	Kährs Supreme	Reaction To Fire	EN13501-1	Cfl-s1
		Collection	Royal Collection	Formaldehyde Emission Content PCP	EN717-1	E1
Design features	Microbevelled 4-sided,	Resandable	2-4 times			
	Brushed, Smoked	Natural/Stained	Stained		CEN/TR14823	≤ 5 ppm
Dimensions	305 x 2400 mm	Brinell Value	3,7	Breaking Strength N/mm²	EN1533	NPD
Weight per Package	30 kg	loint	Tongue & Groove			
Area per Package	2.9 m ²					
Area per pallet	79.1 m ²	Floor heating	Yes	Thermal Conductivity	EN12664	0,09 W/mK
Package info	Packages may contain start and stop boards.	Warranty	30 years			
		Wear-layer material	Hardwood	Thermal Resista	ance R-Value	.194 (m2K/W)
		Wear Layer Thickness	3.5 mm	Biological Durability	EN350-2	Class 1
DETAIL DESCRIPTION		Core material	Pine/Spruce lamella	CARB2		Compliant
•All naturally occuring wood colour variations allowed, from light to dark brown. Sapwood may occur. The product includes very large sound and black knots and cracks. Knots and cracks will be present in all sizes and numbers. •The product may		Thickness	18 mm	Slipperiness	CEN/TS15676	'
		Installation method	Glue-down			
		Surface Colour	Grey			

COLOUR CHANGE

floor itself.

Stained product - noticable color change over time

continue to develop their rustic nature after the floor has been installed, splits and cracks that occur after installation are normal and should be considered part of the timbers natural character.

•The product can be used in connection with floor heating, however the Thermal Resistance (m2K/W) value is above the limit to be classified as suitable for floor heating. This means that the effect of the floor heating will be less but not harmful for the

Other products in this collection









Oak Sanssouci

Oak Chillon

Oak Buckingham

Oak Schönbrunn

CERTIFICATES











Descriptions & Imagery

All samples, images and product description, plus photo and brochure specifications are there for the sole purpose of giving an approximate idea of the items described in them. They shall not form part of the contract or have any contractual force and should be viewed for illustrative purposes only. We cannot guarantee that your computer's display or the quality of the print will accurately reflect the colour of the products. Your product may vary slightly from the images within this literature.