



OAK SANSSOUCI

The smoked stone hues on this single-strip oak floor from the Royal Collection, enhance the earth undertones and balance the natural contrasts in the wood. Each board is carefully brushed to bring out the character of the grain and highlight the natural texture of the wood. Four-sided bevelling at the edges ensures a classic, full plank look and feel.

PRODUCT DETAILS		
Product type / Construction	Wood Floors / 3-layer parquet	
Article Number / EAN Code	181XDDEK26KW240 / 7393969047081	
Design / Wood Species	Plank / Oak	
Surface treatment /	Oil / Natural	
Natural/Stained		
Design features	Microbevelled 4-sided, Brushed, Smoked	
Width x Length x Thickness	305 x 2400 x 18 mm	
Weight per package / per	30 kg / 10.34 kg	
m2		
Area per package / per	2.93 m ² / 79.1 m ²	
pallet		
Grading	Dynamic	
Joint	Tongue & Groove	
Installation method	Glue-down	
Floor heating	Yes	
Wear leayer material /	Hardwood / 3.5 mm	
thickness		
Resandable	2-4 times	
Core material	Pine/Spruce	
Hardness (Brinell) value /	3,7 / 2.2 - 5.9	
range		

PRODU	ICT.	DETAIL	<
PRODU	, C I	DETAIL	$_{-}$

Warranty	30 years	
TECHNICAL PROPERTIES	5	
Moisture content	EN13183	7%±2%
Minimun Mean Density		>500 kg/m³
kg/m³		
Reaction To Fire	EN13501-1	Cfl-s1
Formaldehyde Emission	EN717-1	E1
Content PCP	CEN/TR14823	≤ 5 ppm
Breaking Strength N/mm²	EN1533	NPD
Thermal Conductivity	EN12664	0,09 W/mK
Thermal Resistance R-Value	!	.194 (m2K/W)
Biological Durability	EN350-2	Class 1
CARB2		Compliant
Slip resistance	CEN/TS15676	NPD













DETAILED DESCRIPTION

- •All naturally occuring wood colour variations allowed, from light to dark brown. Sapwood may occur. The smoked design is likely to enhance the naturally occuring wood color variations and create further contrast between light and dark. The product includes very large sound and black knots and cracks. Knots and cracks will be present in all sizes and numbers.
- •The product may continue to develop their rustic nature after the floor has been installed, splits and cracks that occur after installation are normal and should be considered part of the timbers natural character.
- •The product can be used in connection with floor heating, however the Thermal Resistance (m2K/W) value is above the limit to be classified as suitable for floor heating. This means that the effect of the floor heating will be less but not harmful for the floor itself.

Oil: This floor should be oiled immediately after installation.

Colour change: Smoked product - noticable color change over time.

Descriptions & Imagery

Other products in this collection









OAK SANSSOUCI

OAK CHILLON

OAK BUCKINGHAM

OAK SCHÖNBRUNN