



OAK BUCKINGHAM

This classic single-strip oak floor from the Royal Collection features a misty white transparent stain, which enhances the organic design and allows distinctive gradations in the wood to come through. Four-sided micro-bevelling at the edges ensures a full plank look and feel. Each board is carefully brushed to bring out the character of the grain and highlight the natural texture of the wood.

PRODUCT DETAILS		
Product type / Construction	Wood Floors / 3-layer parquet	
Article Number / EAN Code	181XADEK25KW240 / 7393969047067	
Design / Wood Species	Plank / Oak	
Surface treatment /	Oil / Stained	
Natural/Stained		
Design features	Microbevelled 4-sided, Brushed	
Width x Length x Thickness	305 x 2400 x 18 mm	
Weight per package / per	30 kg / 10.34 kg	
m2		
Area per package / per	2.93 m ² / 79.1 m ²	
pallet		
Grading	Dynamic	
Joint	Tongue & Groove	
Installation method	Glue-down	
Floor heating	Yes	
Wear leayer material /	Hardwood / 3.5 mm	
thickness		
Resandable	2-4 times	
Core material	Pine/Spruce	
Hardness (Brinell) value /	3,7 / 2.2 - 5.9	
range		

000	LICT	DETAIL	_
PROD	UCI	DETAIL	_S

Warranty	30 years	
TECHNICAL PROPERTIES	5	
Moisture content	EN13183	7%±2%
Minimun Mean Density		>500 kg/m³
kg/m³		
Reaction To Fire	EN13501-1	Cfl-s1
Formaldehyde Emission	EN717-1	E1
Content PCP	CEN/TR14823	≤ 5 ppm
Breaking Strength N/mm²	EN1533	NPD
Thermal Conductivity	EN12664	0,09 W/mK
Thermal Resistance R-Value	1	.194 (m2K/W)
Biological Durability	EN350-2	Class 1
CARB2		Compliant
Slip resistance	CEN/TS15676	NPD











DETAILED DESCRIPTION

- •All naturally occuring wood colour variations allowed, from light to dark brown. Sapwood may occur. The product includes very large sound and black knots and cracks. Knots and cracks will be present in all sizes and numbers.
- •The product may continue to develop their rustic nature after the floor has been installed, splits and cracks that occur after installation are normal and should be considered part of the timbers natural character.
- •The product can be used in connection with floor heating, however the Thermal Resistance (m2K/W) value is above the limit to be classified as suitable for floor heating. This means that the effect of the floor heating will be less but not harmful for the floor itself.

Oil: This floor should be oiled immediately after installation.

Colour change: Stained product - noticable color change over time

Packages may contain start and stop boards.

www.kahrs.com | ©Kährs **Descriptions & Imagery** All samples, images and product description, plus photo and brochure specifications are there for the sole purpose of giving an approximate idea of the items 2025-11-11

Other products in this collection









OAK SANSSOUCI

OAK CHILLON

OAK BUCKINGHAM

OAK SCHÖNBRUNN