



OAK CADENCE

PRODUCT DETAILS	
Product type / Construction	Wood Flooring / 3-layer engineered
Article Number / EAN Code	13103AEK1PKW185 / 7393969107358
Design / Wood Species	1-strip / White Oak
Surface Treatment /	Matte finish / Stained
Natural/Stained	
Width x Length x Thickness	5 x 73 1/4 x 1/2"
Weight per package / per	28 lbs / 16.9 lbs
m2	
Area per package / per	17.8 sqft / 1120.3 sqft
pallet	
Grading	Variation
Joint	Woodloc® 5G
Installation method	Floating, Glue-Down
Floor heating	Yes
Wear leayer material /	Hardwood / 1/8"
thickness	
Resandable	2 times
Core material	Pine/Spruce lamella
Hardness (Brinell) value /	3,7 / 2.2 - 5.9
range	
LRV / LRV Std1 / LRV Std2	56 / 1.9 / 3.8

PRODI	ICT	DETAIL	ς
FILOD	ノし।	DLIAIL	

Warranty	25 years	
TECHNICAL PROPERTIES	5	
Moisture content	EN13183	7%±2%
Minimun Mean Density kg/m³		>500 kg/m³
Reaction To Fire	EN13501-1	Dfl-s1
Formaldehyde Emission	EN717-1	E1
Content PCP	CEN/TR14823	≤ 5 x 10-6n
Breaking Strength N/mm²	EN1533	NPD
Thermal Conductivity	EN12664	0,08 W/mK
Thermal Resistance R-Value		.15 (m2K/W)
Biological Durability	EN350-2	Class 1
CARB2		Compliant
Slip resistance	CEN/TS15676	NPD







DETAILED DESCRIPTION

Colour change: Stained product - noticeable color change over time.

Packages may contain start and stop boards.

Other products in this collection



Oak Mostra