

SPREEWALD CLW 218

The Kährs Luxury Tiles Click floors has been designed for home and public environments that require floors with adhesive-free installation that are both beautiful and tough. They come in a variety of wood and stone designs. Maximum durability and stability is achieved through the rigid core and the unique 5G locking technology, enabling easy installation by clicking the tiles together. The Click floors are made from virgin vinyl with a rigid core. All floors in the collection have IXPE sound reducing backing, effectively controlling noise. The surface is treated with a strong ceramic coating resistant to wear and tear, scratching and water. They can be installed on an existing floor, making the Click floors ideal to use in renovation projects or when you want to retain the existing floor. Just like all our other Luxury Tiles floors, they are phthalate-free.

PRODUCT DETAILS		TECHNICAL PROPERTIES			
Article Number	LTCLW2202-218	Application	EN ISO	23/33/42	, 1 (1 , 1 , 1 (1 , 1
Dimensions	8 5/8 x 72 "		10874		
Weight per Package	35.1 lbs	Emission of formaldehyde		E1	
Area per Package	17.3 sqft	Reaction To Fire	EN13501-1	Bfl-s1	B _{ir} s1
Area per pallet	1178.6 sqft	Formaldehyde Emission	EN717-1	E1	
Construction	Click 6 mm Impression	Thermal Resistance R-Value		0.035 (m2K/W)	Corp.
FACTS		Residual indentation	EN ISO	< 0.2 mm (*with underlayment	t) 🗊
Design	Wood design		24343-1		
Range	Luxury Tiles	Dimensional stability	EN ISO 23999	< 0.1 %	K N K V
Collection	Impression Wood Collection	Colour fastness	EN ISO 105-	> 6	37
Joint	Click5G		B02		
Floor heating	Yes	Slip resistance	EN 13893	DS (>0.3)	Kan Ing
		Slip resistance	DIN 51130	R10	DS-
		Statical electrical propensity	EN 1815	< 2 kV (antistatic)	Z

Descriptions & Imagery

All samples, images and product description, plus photo and brochure specifications are there for the sole purpose of giving an approximate idea of the items described in them. They shall not form part of the contract or have any contractual force and should be viewed for illustrative purposes only. We cannot guarantee that your computer's display or the quality of the print will accurately reflect the colour of the products. Your product may vary slightly from the images within this literature.

TECHNICAL PROPERTIES

Scratch resistance	EN16094	Pass with good results	P
Chemical resistance	EN ISO 26987	Pass with good results	
Resistance to bacteria an	ıd fungi	Good	
Impact sound reduction	EN ISO 10140	20 ΔLw dB (IXPE underlayment)	2
Commercial usage classification	EN 14354:201	Class 33 7	

Descriptions & Imagery

All samples, images and product description, plus photo and brochure specifications are there for the sole purpose of giving an approximate idea of the items described in them. They shall not form part of the contract or have any contractual force and should be viewed for illustrative purposes only. We cannot guarantee that your computer's display or the quality of the print will accurately reflect the colour of the products. Your product may vary slightly from the images within this literature.

Other products in this collection



Laponia - Click 6 mm Impression



Foxall - Click 6 mm Impression



Odenwald - Click 6 mm Impression



Balmoral - Click 6 mm Impression



Kelham - Click 6 mm Impression



Spreewald - Click 6 mm Impression



Saham - Click 6 mm Impression



Dovecot - Click 6 mm Impression

Descriptions & Imagery

All samples, images and product description, plus photo and brochure specifications are there for the sole purpose of giving an approximate idea of the items described in them. They shall not form part of the contract or have any contractual force and should be viewed for illustrative purposes only. We cannot guarantee that your computer's display or the quality of the print will accurately reflect the colour of the products. Your product may vary slightly from the images within this literature.