



BALMORAL CLW 218

PRODUKTBEKRIVELSE			TEKNISKE EGENSKABER		
Produkttype / Konstruktion	Vinylgulve / Click SPC LVT		Formaldehyde Emission	EN717-1	E1
Artikelnummer / EAN kode	LTCLW2203-218 / 7393969113168		Thermal Resistance R-Value	0.035 (m2K/W)	
Design	Tile Design		Residual indentation	EN ISO 24343-1	< 0.2 mm (*with underlayment)
Bredde x Længde x Tykkelse	220 x 1829 x 6mm		Dimensional stability	EN ISO 23999	< 0.1 %
Vikt Per pakke / per m2	15,9 kg / 9,88 kg		Colour fastness	EN ISO 105-B02	≥ 6
Overflade pr pakke / pr palle	1,61 m² / 109,5 m²		Slip resistance	EN 13893	DS (>0.3)
FAKTA			Slip resistance	DIN 51130	R10
			Statical electrical propensity	EN 1815	< 2 kV (antistatic)
			Scratch resistance	EN16094	Pass with good results
Fuge	Click5G		Chemical resistance	EN ISO 26988	Pass with good results
Installations vejledning	Flydende		Resistance to bacteria and fungi	Good	
Gulvvarme	Ja		Impact sound reduction	EN ISO 10140	20 ΔLw dB (IXPE underlayment)
Slidlag tykkelse	0,55 mm		Commercial usage classification	EN 14354:2017	Class 33
Garanti	30 år				
TEKNISKE EGENSKABER					
Application	EN ISO 10874	23/33/42			
Emission of formaldehyde	E1				
Reaction To Fire	EN13501-1	Bfl-s1			


Andre produkter i denne kollektion



Sumava - Click 6 mm Impression



Harz - Click 6 mm Impression



Jasmund - Click 6 mm
Impression



Laponia - Click 6 mm Impression



Odenwald - Click 6 mm
Impression




Kelham - Click 6 mm Impression



Saham - Click 6 mm Impression



Foxall - Click 6 mm Impression



Balmoral - Click 6 mm
Impression



Spreewald - Click 6 mm
Impression



Dovecot - Click 6 mm
Impression