



FOXALL CLICK 6 MM

The Kährs Luxury Tiles Click floors has been designed for home and public environments that require floors with adhesive-free installation that are both beautiful and tough. They come in a variety of wood and stone designs. Maximum durability and stability is achieved through the rigid core and the unique 5G locking technology, enabling easy installation by clicking the tiles together. The Click floors are made from virgin vinyl with a rigid core. All floors in the collection have IXPE sound reducing backing, effectively controlling noise. The surface is treated with a strong ceramic coating resistant to wear and tear, scratching and water. They can be installed on an existing floor, making the Click floors ideal to use in renovation projects or when you want to retain the existing floor. Just like all our other Luxury Tiles floors, they are phthalate-free.

PRODUCT DETAILS			TECHNICAL PROPERTIES		
Product type / Construction	Luxury Vinyl Tiles and	Planks / Click SPC LVT	Thermal Resistance R-Value		0.035 (m2K/W)
Article Number / EAN Code	LTCLW2204-218 / 7393969113175		Residual indentation	EN ISO 24343-1	< 0.2 mm (*with
Design	1-strip				underlayment)
Width x Length x Thickness	220 x 1829 x 6 mm		Dimensional stability	EN ISO 23999	< 0.1 %
Weight per package / per	per package / per 15.9 kg / 9.88 kg		Colour fastness	EN ISO 105-B02	≥ 6
m2			Slip resistance	EN 13893	DS (>0.3)
Area per package / per	1.61 m ² / 109.48 m ²		Slip resistance	DIN 51130	R10
pallet			Statical electrical	EN 1815	< 2 kV (antistatic)
Joint	Click5G		propensity		
Installation method	Floating		Scratch resistance	EN16094	Pass with good results
Floor heating	Yes		Chemical resistance	EN ISO 26987	Pass with good results
Wear leayer thickness	0.55 mm		Effect of castor chair	EN 425	Suitable (25.000 cycles)
Warranty	30 years		Resistance to bacteria and		Good
TECHNICAL PROPERTIES			fungi		
Application	EN ISO 10874	23/33/42	mpact sound reduction	EN ISO 10140	20 ΔLw dB (IXPE
Emission of formaldehyde	EIV 130 1007 +	E1	<u> </u>		underlayment)
Reaction To Fire	EN13501-1	Bfl-s1	Commercial usage	EN 14354:2017	Class 33
Formaldehyde Emission	EN717-1	E1	classification		
Torridacity de Litilission	LIN/I/I	L1			

Other products in this collection







HARZ CLICK



JASMUND CLICK



LAPONIA CLICK



SAHAM CLICK



FOXALL CLICK



SPREEWALD CLICK



DOVECOT CLICK