



Impression Wood Collection



SAHAM CLICK XXL 6 MM

The Kährs Luxury Tiles Click floors has been designed for home and public environments that require floors with adhesive-free installation that are both beautiful and tough. They come in a variety of wood and stone designs. Maximum durability and stability is achieved through the rigid core and the unique 5G locking technology, enabling easy installation by clicking the tiles together. The Click floors are made from virgin vinyl with a rigid core. All floors in the collection have IXPE sound reducing backing, effectively controlling noise. The surface is treated with a strong ceramic coating resistant to wear and tear, scratching and water. They can be installed on an existing floor, making the Click floors ideal to use in renovation projects or when you want to retain the existing floor. Just like all our other Luxury Tiles floors, they are phthalate-free.

PRODUCT DETAILS			TECHNICAL PROPERTIES		
Product type / Construction	Luxury Vinyl Tiles and Planks / Click SPC LVT		Reaction To Fire	EN13501-1	Bfl-s1
Article Number / EAN Code	LTCLW2205-218 / 7393969113182		Formaldehyde Emission	EN717-1	E1
Design	Plank		Thermal Resistance R-Value	0.035 (m2K/W)	
Width x Length x Thickness	220 x 1829 x 6 mm		Residual indentation EN	< 0.2 mm (*with	
Weight per package / per m2	15.9 kg / 9.88 kg		ISO 24343-1	underlayment)	
Area per package / per pallet	1.61 m² / 109.48 m²		Dimensional stability	EN ISO 23999	< 0.1 %
Joint	Click5G		Colour fastness	EN ISO 105-B02	≥ 6
Installation method	Floating		Slip resistance	EN 13893	DS (>0.3)
Floor heating	Yes		Slip resistance	DIN 51130	R10
Wear leayer thickness	0.55 mm		Statical electrical propensity	EN 1815	< 2 kV (antistatic)
Warranty	30 years		Scratch resistance	EN16094	Pass with good results
TECHNICAL PROPERTIES			Chemical resistance	EN ISO 26987	Pass with good results
Application	EN ISO 10874	23/33/42	Effect of castor chair	EN 425	Suitable (25.000 cycles)
Effect of furniture leg	EN ISO 16581	No visible damage/Change	Resistance to bacteria and fungi	Good	
Impact resistance	>1800 mm		Impact sound reduction	EN ISO 10140	20 ΔLw dB (IXPE underlayment)
Emission of formaldehyde	E1		Commercial usage classification	EN 14354:2017	Class 33

Other products in this collection



SUMAVA CLICK XXL



HARZ CLICK XXL



JASMUND CLICK XXL



LAPONIA CLICK XXL



SAHAM CLICK XXL



FOXALL CLICK XXL



SPREEWALD CLICK XXL



DOVECOT CLICK XXL