

## SAHAM CLICK 6 MM

The Kährs Luxury Tiles Click floors has been designed for home and public environments that require floors with adhesive-free installation that are both beautiful and tough. They come in a variety of wood and stone designs. Maximum durability and stability is achieved through the rigid core and the unique 5G locking technology, enabling easy installation by clicking the tiles together. The Click floors are made from virgin vinyl with a rigid core. All floors in the collection have IXPE sound reducing backing, effectively controlling noise. The surface is treated with a strong ceramic coating resistant to wear and tear, scratching and water. They can be installed on an existing floor, making the Click floors ideal to use in renovation projects or when you want to retain the existing floor. Just like all our other Luxury Tiles floors, they are phthalate-free.

PRODUCT DETAILS			TECHNICAL PROPERTIES		
Product type / Construction	Luxury Vinyl Tiles and Planks / Click SPC LVT		Formaldehyde Emission	EN717-1	E1
Article Number / EAN Code	LTCLW2205-218 / 7393969113182		Thermal Resistance R-Value		0.035 (m2K/W)
Design	Plank		Residual indentation EN		< 0.2 mm (*with
Width x Length x Thickness	220 x 1829 x 6 mm		ISO 24343-1		underlayment)
Weight per package / per	15.9 kg / 9.88 kg		Dimensional stability	EN ISO 23999	< 0.1 %
m2			Colour fastness	EN ISO 105-B02	≥6
Area per package / per	1.61 m <sup>2</sup> / 109.48 m <sup>2</sup>		Slip resistance	EN 13893	DS (>0.3)
pallet			Slip resistance	DIN 51130	R10
Joint	Click5G		Statical electrical	EN 1815	< 2 kV (antistatic)
Installation method	Floating		propensity		
Floor heating	Yes		Scratch resistance	EN16094	Pass with good results
Wear leayer thickness	0.55 mm		Chemical resistance	EN ISO 26987	Pass with good results
Warranty	30 years		Effect of castor chair	EN 425	Suitable
TECHNICAL PROPERTIES			Resistance to bacteria and		Good
Application	EN ISO 10874	23/33/42	fungi		
Effect of furniture leg	EN ISO 16581	No visible damage/Change	<ul> <li>Impact sound reduction</li> </ul>	EN ISO 10140	20 <b>Δ</b> Lw dB (IXPE
Emission of formaldehyde		E1			underlayment)
Reaction To Fire	EN13501-1	Bfl-s1	<ul> <li>Commercial usage</li> <li>classification</li> </ul>	EN 14354:2017	Class 33

## Descriptions & Imagery

All samples, images and product description, plus photo and brochure specifications are there for the sole purpose of giving an approximate idea of the items described in them. They shall not form part of the contract or have any contractual force and should be viewed for illustrative purposes only. We cannot guarantee that your computer's display or the quality of the print will accurately reflect the colour of the products. Your product may vary slightly from the images within this literature.

## Other products in this collection





HARZ CLICK





JASMUND CLICK





SPREEWALD CLICK



LAPONIA CLICK



DOVECOT CLICK

SAHAM CLICK

FOXALL CLICK