



0.035 (m2K/W)

ODENWALD CLW 218

The Kährs Luxury Tiles Click floors has been designed for home and public environments that require floors with adhesive-free installation that are both beautiful and tough. They come in a variety of wood and stone designs. Maximum durability and stability is achieved through the rigid core and the unique 5G locking technology, enabling easy installation by clicking the tiles together. The Click floors are made from virgin vinyl with a rigid core. All floors in the collection have IXPE sound reducing backing, effectively controlling noise. The surface is treated with a strong ceramic coating resistant to wear and tear, scratching and water. They can be installed on an existing floor, making the Click floors ideal to use in renovation projects or when you want to retain the existing floor. Just like all our other Luxury Tiles floors, they are phthalate-free.

PRODUCT DETAILS			TECHNICAL PROPERTIES
Product type / Construction	Luxury Vinyl Tiles and Pla	nks / Click SPC LVT	Thermal Resistance R-Value
Article Number / EAN Code	LTCLW2207-218 / 73939	69113212	Residual indentation
Design	Tile Design		_
Width x Length x Thickness	220 x 1829 x 6 mm		Dimensional stability
Weight per package / per	15.9 kg / 9.88 kg		Colour fastness
m2			Slip resistance
Area per package / per	1.61 m ² / 109.5 m ²		Slip resistance
pallet			Statical electrical
Joint	Click5G		propensity
Installation method	Floating		Scratch resistance
Floor heating	Yes		Chemical resistance
Wear leayer thickness	0.55 mm		Resistance to bacteria and
Warranty	30 years		fungi
TECHNICAL PROPERTIES			Impact sound reduction
Application	EN ISO 10874	23/33/42	Commercial usage
Emission of formaldehyde		E1	— classification
Reaction To Fire	EN13501-1	Bfl-s1	Ciassification
Formaldehyde Emission	EN717-1	E1	_

esidual indentation	EN ISO 24343-1	< 0.2 mm (*with
		underlayment)
monsional stability	EN ICO 22000	< 0.1.06

		underlayment)
Dimensional stability	EN ISO 23999	< 0.1 %
Colour fastness	EN ISO 105-B02	≥ 6
Slip resistance	EN 13893	DS (>0.3)
Slip resistance	DIN 51130	R10
Statical electrical	EN 1815	< 2 kV (antistatic)
propensity		
Scratch resistance	EN16094	Pass with good results
Chemical resistance	EN ISO 26987	Pass with good results
Resistance to bacteria and		Good
fungi		
Impact sound reduction	EN ISO 10140	20 Δ Lw dB (IXPE
		underlayment)
Commercial usage	EN 14354:2017	Class 33
classification		

Other products in this collection



SUMAVA - CLICK 6 MM IMPRESSION



HARZ - CLICK 6 MM IMPRESSION



JASMUND - CLICK 6 MM IMPRESSION



LAPONIA - CLICK 6 MM IMPRESSION



SAHAM - CLICK 6 MM IMPRESSION



FOXALL - CLICK 6 MM IMPRESSION



SPREEWALD - CLICK 6 MM IMPRESSION



DOVECOT - CLICK 6 MM IMPRESSION