




LAPONIA CLICK XXL 6 MM

PRODUKTBESKRIVELSE			TEKNISKE EGENSKABER		
Produkttype / Konstruktion	Vinylgulve / Click SPC LVT		Formaldehyde Emission	EN717-1	E1
Artikelnummer / EAN kode	LTCLW2208-218 / 7393969113229		Thermal Resistance R-Value	0.035 (m2K/W)	
Design	1-stav		Residual indentation	EN ISO 24343-1	< 0.2 mm (*with underlayment)
Bredde x Længde x Tykkelse	220 x 1829 x 6mm		Dimensional stability	EN ISO 23999	< 0.1 %
Vikt Per pakke / per m2	15,9 kg / 9,88 kg		Colour fastness	EN ISO 105-B02	≥ 6
Overflade pr pakke / pr palle	1,61 m² / 109,48 m²		Slip resistance	EN 13893	DS (>0.3)
FAKTA			Slip resistance	DIN 51130	R10
			Statical electrical propensity	EN 1815	< 2 kV (antistatic)
			Scratch resistance	EN16094	Pass with good results
			Chemical resistance	EN ISO 26988	Pass with good results
			Effect of castor chair	EN 425	Suitable (25.000 cycles)
			Resistance to bacteria and fungi	Good	
TEKNISKE EGENSKABER			Impact sound reduction	EN ISO 10140	20 ΔLw dB (IXPE underlayment)
Application	EN ISO 10874	23/33/42	Commercial usage classification	EN 14354:2017	Class 33
Emission of formaldehyde		E1			
Reaction To Fire	EN13501-1	Bfl-s1			


Andre produkter i denne kollektion



SUMAVA CLICK XXL



HARZ CLICK XXL




JASMUND CLICK XXL



LAPONIA CLICK XXL



SAHAM CLICK XXL



FOXALL CLICK XXL



SPREEWALD CLICK XXL



DOVECOT CLICK XXL