



Impression Stone Collection



TALUNG CLICK XXL 6 MM

The Kährs Luxury Tiles Click floors has been designed for home and public environments that require floors with adhesive-free installation that are both beautiful and tough. They come in a variety of wood and stone designs. Maximum durability and stability is achieved through the rigid core and the unique 5G locking technology, enabling easy installation by clicking the tiles together. The Click floors are made from virgin vinyl with a rigid core. All floors in the collection have IXPE sound reducing backing, effectively controlling noise. The surface is treated with a strong ceramic coating resistant to wear and tear, scratching and water. They can be installed on an existing floor, making the Click floors ideal to use in renovation projects or when you want to retain the existing floor. Just like all our other Luxury Tiles floors, they are phthalate-free.

PRODUCT DETAILS

Product type / Construction	Luxury Vinyl Tiles and Planks / Click SPC LVT	
Article Number / EAN Code	LTCLS3102-457 / 7393969113243	
Design	Tile Design	
Width x Length x Thickness	457 x 914.4 x 6 mm	
Weight per package / per m2	24.7 kg / 9.84 kg	
Area per package / per pallet	2.51 m ² / 100.4 m ²	
Joint	Click5G	
Installation method	Floating	
Floor heating	Yes	
Wear leayer thickness	0.55 mm	
Warranty	30 years	

TECHNICAL PROPERTIES

Application	EN ISO 10874	23/33/42
Emission of formaldehyde		E1
Reaction To Fire	EN13501-1	Bfl-s1
Formaldehyde Emission	EN717-1	E1

TECHNICAL PROPERTIES

Thermal Resistance R-Value		0.035 (m2K/W)
Residual indentation	EN ISO 24343-1	< 0.2 mm (*with underlayment)
Dimensional stability	EN ISO 23999	< 0.1 %
Colour fastness	EN ISO 105-B02	≥ 6
Slip resistance	EN 13893	DS (>0.3)
Slip resistance	DIN 51130	R10
Statical electrical propensity	EN 1815	< 2 kV (antistatic)
Scratch resistance	EN16094	Pass with good results
Chemical resistance	EN ISO 26987	Pass with good results
Effect of castor chair	EN 425	Suitable (25.000 cycles)
Resistance to bacteria and fungi		Good
Impact sound reduction	EN ISO 10140	20 ΔLw dB (IXPE underlayment)
Commercial usage classification	EN 14354:2017	Class 33



Descriptions & Imagery

All samples, images and product description, plus photo and brochure specifications are there for the sole purpose of giving an approximate idea of the items described in them. They shall not form part of the contract or have any contractual force and should be viewed for illustrative purposes only. We cannot guarantee that your computer's display or the quality of the print will accurately reflect the colour of the products. Your product may vary slightly from the images within this literature.

Other products in this collection



KILIMANJARO CLICK XXL



GROSSGLOCKNER CLICK XXL



ULTAR CLICK XXL



TALUNG CLICK XXL



ATHOS CLICK XXL



OLYMPUS CLICK XXL



AMARO CLICK XXL



ANETO CLICK XXL