



- CLICK 6 MM IMPRESSION

DESCRIZIONE DEL PRODOTTO		
Codice articolo / Codice	LTCLS3103-457 / 7393969113250	
EAN		
Design	Tile Design	
Larghezza x Lunghezza x	457 x 914,4 x 6 mm	
Spessore		
Peso per confezione / per	24,7 kg / 9,84 kg	
m2		
Mq. per confezione / pr	2,51 m ² / 100,4 m ²	
pallet		
INFORMAZIONI		
Incastro	Click5G	
Metodi di posa	Flottante	
Riscaldamento a pavimento	Si	
Strato superficiale spessore	0,55 mm	
CADATTERICTICALE TECNIA		

CARATTERISTICHE TECNICHE

CARATTERISTICHE TECNICHE			
Application	EN ISO 10874	23/33/42	
Emission of formaldehyde		E1	
Classe di reazione al fuoco	EN13501-1	Bfl-s1	
Classe di emissione di	EN717-1	E1	
formaldeide			
Resistenza termica valore R		0.035 (m2K/W)	

CARATTERISTICHE TECNICHE

Residual indentation	EN ISO 24343-1	< 0.2 mm (*with
		underlayment)
Dimensional stability	EN ISO 23999	< 0.1 %
Test Colour fastness	EN ISO 105-B02	≥ 6
Slip resistance	EN 13893	DS (>0.3)
Slip resistance	DIN 51130	R10
Statical electrical	EN 1815	< 2 kV (antistatic)
propensity		
Scratch resistance	EN16094	Pass with good results
Resistance to bacteria and		Good
fungi		
Impact sound reduction	EN ISO 10140	20 Δ Lw dB (IXPE
		underlayment)
Commercial usage	EN 14354:2017	Class 33
classification		







Altri prodotti di questa collezione



Kilimanjaro - Click 6 mm Impression



Grossglockner - Click 6 mm Impression



- Click 6 mm Impression



- Click 6 mm Impression



- Click 6 mm Impression



- Click 6 mm Impression



- Click 6 mm Impression



- Click 6 mm Impression