



OLYMPUS CLS 457

The Kährs Luxury Tiles Click floors has been designed for home and public environments that require floors with adhesive-free installation that are both beautiful and tough. They come in a variety of wood and stone designs. Maximum durability and stability is achieved through the rigid core and the unique 5G locking technology, enabling easy installation by clicking the tiles together. The Click floors are made from virgin vinyl with a rigid core. All floors in the collection have IXPE sound reducing backing, effectively controlling noise. The surface is treated with a strong ceramic coating resistant to wear and tear, scratching and water. They can be installed on an existing floor, making the Click floors ideal to use in renovation projects or when you want to retain the existing floor. Just like all our other Luxury Tiles floors, they are phthalate-free.

PRODUCT DETAILS			٦
Product type / Construction	Luxury Vinyl Tiles / Click 6 mm Impression		F
Article Number / EAN Code	LTCLS3104-457 / 7393969113267		
Design	Stone design		
Width x Length x Thickness	457 x 914.4 x 6 mm		(
Weight per package / per	24.7 kg / 9.84 kg		
m2			9
Area per package / per	2.51 m ² / 100.4 m ²		
pallet			<u> </u>
Joint	Click5G		
Installation method	Floating		(
Floor heating	Yes		F
Wear leayer thickness	0.55 mm		f
TECHNICAL PROPERTIES			ī
Application	EN ISO 10874	23/33/42	
Emission of formaldehyde		E1	— (
Reaction To Fire	EN13501-1	Bfl-s1	
Formaldehyde Emission	EN717-1	E1	
Thermal Resistance R-Value		0.035 (m2K/W)	

TECHNICAL PROPERTIE	S
---------------------	---

Residual indentation	EN ISO 24343-1	< 0.2 mm (*with
		underlayment)
Dimensional stability	EN ISO 23999	< 0.1 %
Colour fastness	EN ISO 105-B02	≥ 6
Slip resistance	EN 13893	DS (>0.3)
Slip resistance	DIN 51130	R10
Statical electrical	EN 1815	< 2 kV (antistatic)
propensity		
Scratch resistance	EN16094	Pass with good results
Chemical resistance	EN ISO 26987	Pass with good results
Resistance to bacteria and		Good
fungi		
Impact sound reduction	EN ISO 10140	20 Δ Lw dB (IXPE
		underlayment)
Commercial usage	EN 14354:2017	Class 33
classification		











Other products in this collection



Kilimanjaro - Click 6 mm Impression



Grossglockner - Click 6 mm Impression



Ultar - Click 6 mm Impression



Talung - Click 6 mm Impression



Athos - Click 6 mm Impression



Olympus - Click 6 mm Impression



Amaro - Click 6 mm Impression



Aneto - Click 6 mm Impression