




SPREEWALD CLICK XXL 6 MM

The Kährs Luxury Tiles Click floors has been designed for home and public environments that require floors with adhesive-free installation that are both beautiful and tough. They come in a variety of wood and stone designs. Maximum durability and stability is achieved through the rigid core and the unique 5G locking technology, enabling easy installation by clicking the tiles together. The Click floors are made from virgin vinyl with a rigid core. All floors in the collection have IXPE sound reducing backing, effectively controlling noise. The surface is treated with a strong ceramic coating resistant to wear and tear, scratching and water. They can be installed on an existing floor, making the Click floors ideal to use in renovation projects or when you want to retain the existing floor. Just like all our other Luxury Tiles floors, they are phthalate-free.

PRODUCT DETAILS

Article Number / EAN-code	LTCLW2202-218 / 7393969113144
Construction	Click SPC LVT
Design	Plank
Features	Microbevelled 4-sided, Wood design, XXL Format, Integrated sound reduction, Synchronized embossing
Width x Length x Thickness	220 mm x 1829 mm x 6 mm
Weight per package / Weight per m² (kg)	15.9 kg / 9.88 kg
Area per Package (m²) / Area per pallet (m²)	1.61 m² / 109.48 m²
Joint	Click5G
Installation method	Floating
Floor heating	Yes
Wear Layer Thickness approx. (mm)	0.55 mm
LRV	22.7
Warranty	30 years
Collection	Impression Wood Collection

PRODUCT DETAILS

Joint	Click5G

TECHNICAL PROPERTIES

Impact resistance (mm	big ball), EN 13329	>1800 mm
Thermal Resistance R-Value		0.035 (m2K/W)
Statical electrical propensity	EN 1815	< 2 kV (antistatic)
Slip resistance	EN 13893	DS (>0.3)
Slip resistance	DIN 51130	R10
Resistance to bacteria and fungi		Good
Scratch resistance	EN16094	Pass with good results
Residual indentation	EN ISO 24343-1 (2.5 h)	< 0.2 mm (*with underlayment)
Reaction To Fire	EN13501-1	Bfl-s1
Impact sound reduction	EN ISO 10140	20 ΔLw dB (IXPE underlayment)
Emission of formaldehyde (HCHO)	EN 14041	E1
Dimensional stability	EN ISO 23999	< 0.1 %
Commercial usage classification	EN 14354:2017	Class 33
Colour fastness	EN ISO 105-B02	≥ 6
Chemical resistance	EN ISO 26987	Pass with good results
Application	EN ISO 10874	23/33/42

Descriptions & Imagery: All samples, images and product description, plus photo and brochure specifications are therefor the sole purpose of giving an approximate idea of the items described in them.They shall not form part of the contract or have any contractual force and should be viewed for illustrative purposes only. We cannot guarantee that your computer's display or the quality of the print will accurately reflect the colour of the products.Your product may vary slightly from the images within this literature.

OTHER PRODUCTS IN THIS COLLECTION



SUMAVA CLICK XXL



DOVECOT CLICK XXL



SPREEWALD CLICK XXL



FOXALL CLICK XXL



SAHAM CLICK XXL



LAPONIA CLICK XXL



JASMUND CLICK XXL



HARZ CLICK XXL

KÄHRS LT CLICK 6 MM IMPRESSION XXL WOOD SWATCH