

TECHNICAL DATA

KÄHRS ZERO SHEET

ENOMER® CONTRACT SHEET FLOORING


PRODUCT		
Zero Sheet	EN 14565	PVC- and plasticizer-free Enomer® flooring
Application	EN ISO 10874	23/34/43
SPECIFICATION		
Thickness	EN ISO 24346	2.0 mm
Weight	EN ISO 23997	3100 g/m²
Roll length	EN ISO 24341	10 - 25 m
Width	EN ISO 24341	145 cm
PRODUCT PROPERTIES		
PROPERTY	TEST METHOD	RESULT
Indoor air certifications		M1, AgBB, Floorscore
Fire resistance	EN 13501-1	C _{fi} -s1
Residual indentation	EN ISO 24343-1 (2.5 h)	ca. 0.03 mm
Slip resistance	EN 13893 DIN 51130	DS (> 0.3) R9
Electrical propensity	EN 1815	≤ 2 kV (antistatic)
Wear and scratch resistance	EN 660-2 ISO 5470-1	≤ 2.0 mm³ (Class T) 0.05 g/1000 cycles
Effect of castor chair	EN ISO 4918	Suitable
Dimensional stability	EN ISO 23999 (50 °C/6 h)	< 0.2%
Colour fastness	EN ISO 105-B02	≥ 6
Flexibility	EN ISO 24344 Method A	10 mm
Chemical Resistance	EN ISO 26987	Excellent
Underfloor heating		Suitable (max. +28 °C)
Insulation resistance	EN 1081	> 100 GΩ
Watertightness	EN 13553 Annex A	Pass
Thermal conductivity	EN 12667	0.22 W/mK
Tensile strength of seam	EN 684	> 400 N / 50 mm
Resistance to bacteria and fungi	ISO 846	Good




COLLECTION

KÄHRS ZERO SHEET


ENOMER® CONTRACT SHEET FLOORING




BLUE MOON
105752
NCS S 5020-R80B
LRV 15.9




BLUE ORCHID
105758
NCS S 4020-R90B
LRV 22.4




AQUAMARINE
105753
NCS S 1020-B10G
LRV 52.7




SERENITY
105754
NCS S 2010-R90B
LRV 46.4




DENIM
105759
NCS S 6020-B
LRV 14.3




OZONE
105755
NCS S 7010-B10G
LRV 11.0




ICE GREY
105714
NCS S 2502-B
LRV 45.6




METEORITE
105715
NCS S 3502-B
LRV 33.0




STORMY
105716
NCS S 6502-B
LRV 16.9




MIDNIGHT
105706
NCS S 8502-B
LRV 6.3



GRAPHITE
105705
NCS S 7500-N
LRV 10.2



STONE GREY
105704
NCS S 6000-N
LRV 20.4



PEWTER
105703
NCS S 4500-N
LRV 28.8




CAPE COD
105702
NCS S 2500-N
LRV 49.8




PEARL
105701
NCS S 1500-N
LRV 60.7




SILVER GREY
105711
NCS S 3000-N
LRV 46.1




CONCRETE
105712
NCS S 3502-Y
LRV 36.0



GRANITE
105713
NCS S 4502-Y
LRV 25.3




MOROCCO
105723
NCS S 4010-Y30R
LRV 35.1




DUSTY
105722
NCS S 2005-Y30R
LRV 48.3




MOON ROCK
105721
NCS S 1505-Y30R
LRV 63.6




CORUNDUM
105724
NCS S 6005-Y50R
LRV 17.6




CURRY
105776
NCS S 3040-Y30R
LRV 28.2




SUNBEAM
105729
NCS S 2030-Y20R
LRV 46.2




TERRACOTTA
105743
NCS S 2060-Y80R
LRV 21.0




CAROTENE
105732
NCS S 2060-Y40R
LRV 30.4




MAYAN MAIZE
105728
NCS S 1060-Y
LRV 50.8




MESA
105773
NCS S 3030-Y60R
LRV 25.4



SPRUCE
105763
NCS S 3040-G30Y
LRV 26.7




THORN APPLE
105762
NCS S 2030-G60Y
LRV 42.7




APPLE MINT
105761
NCS S1020-G50Y
LRV 57.1




AMBROSIA
105764
NCS S 2005-G30Y
LRV 49.7




PINE
105768
NCS S 5010-G30Y
LRV 23.1




SEA FOAM
105765
NCS S 4005-G20Y
LRV 32.8




JADE
105766
NCS S 6005-B80G
LRV 18.6



VERDE
105767
NCS S 7005-B80G
LRV 11.3



MYSTIC
105775
NCS S 7005-R80B
LRV 12.5



ASPHALT
105774
NCS S 7502-R
LRV 10.7

