



Herringbone 103.3 x 590.5 x 6 x 0.7 mm
0,977 m²/box, 112 box/pallet



Chevron 145 x 665.4 x 6 x 0.7 mm
1,351 m²/box, 72 box/pallet

TECHNICAL DATA

KÄHRS LUXURY TILES

CLICK 6 MM SENSATION COLLECTION

King Size Plank, Herringbone, Chevron



King Size Plank 241.3 x 1815 x 6 x 0.7 mm
1,752 m²/box, 68 box/pallet

PRODUCT

Click LVT Rigid Core SPC + 1 mm PVC foam underlay	EN ISO 10582	Luxury Vinyl Tile
Joint		Unipush / Unizip
Application	EN ISO 10874	23/34

SPECIFICATION

Thickness		EN ISO 24337	6.0 mm (integratedPVC damping)
Weight		EN ISO 24342	10.29 kg/m ²
Wear layer		EN ISO 24346	0.7 mm

PRODUCT PROPERTIES

PROPERTY	TEST METHOD	RESULT
Indoor air certifications		M1, FloorScore, A+
Fire resistance	EN 13501-1	B _{fi} -s1
Residual indentation	EN ISO 24343-1	< 0.15 mm (integrated PVC damping)
Dimensional stability	EN ISO 23999 (80 °C/6 h)	< 0.15%
Colour fastness	EN ISO 105-B02	≥ 6
Slip resistance	EN 13893 DIN 51130	DS (> 0.3)
Electrical propensity	EN 1815	< 2 kV (antistatic)
Wear resistance	EN 16094	≥ 7000 (Method B)
Chemical resistance	EN ISO 26987	Pass with good results
Effect of castor chair	EN 425	25 000 Cycles
Thermal resistance	EN 12667:2001	0.051 m ² K/W
Underfloor heating		Ok (max +27 °C)
Resistance to bacteria and fungi		Good
Impact sound reduction	EN ISO 10140	ΔL _w = 19 dB (integratedPVC damping)
Micro scratch resistance	EN 16094	≤ MSR - A1
Effect of furniture leg	EN 16581	No visible damage

