THE COMPLETE KÄHRS FLOORING SYSTEM

UNDERLAYMENTS



Kährs Combo System



Roll Coverage	100 ft ²	630 ft ²
Roll Length	30′	189′
Roll Width	40"	40"
Thickness	1/8"	1/8"
Roll Weight	3 lbs, 3 oz	21 lbs
Roll Diameter	7 1/8"	16 1/2"
Item Number	710100	710107
Sound Rating	IIC = 68	

- · Helps level the subfloor
- · Provides moisture barrier/ventilation
- · Compressibility-holds its shape under heavy loads
- · Meets requirements for Kährs Lifetime Guarantee
- Mold reducing, inert and non-reactive construction
- · Lightweight with Integrated overlap seal
- · Ideal for radiant heating

Kährs Eco+



Roll Coverage	100 ft ²	450 ft ^{2*}
Roll Length	33′ 4″	75′
Roll Width	3′	6′
Thickness	1/8"	1/8"
Roll Weight	16 lbs	74 lbs
Roll Diameter	7"	11"
Item Number	711100	711450*
Sound Rating	IIC = 70	

*Special Order

- · Excellent acoustical performance
- Meets requirements for Kährs Lifetime Guarantee
- · Lightweight with Integrated overlap seal
- 100% high density memory foam
- Premium polyurethane construction
- · Guaranteed over radiant heat
- · UL GreenGuard GOLD certified
- Breathable moisture barrier;
 Up to 10lbs moisture emission
- Ultra-fresh antimicrobial protection
- Free from formaldehyde, latex, PBDE's
- · Made in part with natural resources
- · 100% recyclable
- Eligible for LEED credits

Kährs QuietStride 2.0



Roll Coverage	300 ft ²
Roll Length	75'
Roll Width	48"
Thickness	1/8"
Roll Weight	120 lbs
Roll Diameter	9"
Item Number	710112
Sound Rating	IIC = 57

- Glue down, floating installations
- Enhances underfoot comfort
- Conceals minor subfloor irregularities
- Always lays flat and will not slip during installation
- Approved for 'double-stick' installations
- 92% recycled tire content and 100% recyclable
- · CRI Green Label +PLUS certified
- · FloorScore certified & Contributes to LEED credits
- Guaranteed over radiant heat
- · Resists mold, mildew, and fungus growth