# **Kahrs Condensed Guide Spec**

### All other information is available at kahrs.com

GUIDE SPECIFICATION

09 64 33.05

#### **KAHRS LINNEA 7**

## For Residential Single Family and

### Multi-Family – Apartments & Condominiums

### **Not Warranted for Commercial Projects**

Kahrs International, Inc. 940 Centre Circle, Suite 1000 Altamonte Springs, FL 32714 Telephone: 407-260-90910 Fax: 407-260-9933

Toll Free: 800-800-5247 http://www.kahrs.com

# SECTION 09 64 33.05 ENGINEERED WOOD STRIP FLOORING

#### 1.1 ENGINEERED WOOD STRIP FLOORING

- A. Product[s]: Subject to compliance with requirements, provide Linnea 7 Collection by Kahrs International Inc.
  - 1. Three layered laminated wood flooring consisting of a sliced plain-sawn wearing layer in choice of wood species, design and finish.
  - 2. Middle core of high-density fiberboard (HDF).
  - 3. Backing layer of pine.
  - 4. Solid tongue and groove construction, 9/32-inch (7-mm) thickness for float-in applications only.
  - 5. Patented Woodloc<sup>TM</sup> joint profile.
  - 6. Length: Manufacturer's standard.
  - 7. Edges: As indicated by product designation above.
  - 8. Finish: Manufacturer's standard UV cured acrylic urethane in color selected by Architect from full range.
  - 9. Wood Species, Design, and Finish [WF-#]: <insert product description from web site>.

#### 1.2 UNDERLAYMENTS

- A. For floating and radiant heat installations:
  - 1. Kahrs Combo-System Foam Underlayment.
  - 2. Use of this product is required by warranty.
- B. Kahrs QuietStride underlayment plus vapor retarder complying with ASTM D 4397, polyethylene sheet not less than 6.0 mils (0.15 mm) thick. Kahrs approved moisture sealer may be substituted for 6.0 mil polyethylene sheet for QuietStride installations.

#### 1.3 ACCESSORY MATERIALS

- A. Wood Trim: In same species and grade as wood flooring, unless otherwise indicated.
  - 1. Wood Base: Manufacturer's standard.
  - 2. Quarter Round Molding: Manufacturer's standard.
  - 3. T- Molding: Manufacturer's standard.
  - 4. Threshold: Tapered on each side and routed at bottom of one side to accommodate wood flooring.
  - 5. Reducer Strip: Manufacturer's standard.
  - 6. Square Nose Reducer Strip: Manufacturer's standard.
  - 7. Use Kahrs cleaner to maintain floor