

Kahrs Condensed Guide Spec
All other information is available at kahrs.com

GUIDE SPECIFICATION

09 64 33.01

AMERICAN NATURALS AMERICAN TRADITIONALS
EUROPEAN NATURALS WORLD NATURALS
SCANDINAVIAN NATURALS

Kahrs International, Inc.
940 Centre Circle, Suite 1000
Altamonte Springs, FL 32714
Telephone: 407-260-9910
Fax: 407-260-9933
Toll Free: 800-800-5247
Web Site: <http://www.kahrs.com>

SECTION 09 64 33.01

ENGINEERED WOOD STRIP FLOORING

PART 1 - PRODUCTS

2.1 ENGINEERED WOOD STRIP FLOORING

- A. Product: Subject to compliance with requirements, provide American Naturals Collection, European Naturals Collection, Scandinavian Naturals by Kahrs International Inc.
1. Three layered laminated wood flooring consisting of a wearing layer in choice of wood species, design and finish.
 2. Middle core of quarter sawn pine fingers providing stability and shape retention.
 3. Backing layer of spruce.
 4. Patented Woodloc™ joint profile for glue down, and float-in installations.
 5. 5/8-inch (15-mm) thickness.
 6. Length: Manufacturer's standard.
 7. Edges: As indicated by product designation above.
 8. Finish: Manufacturer's standard UV cured acrylic urethane finish in color selected by Architect from full range.

Specifier Note: Refer to manufacturer's web site for current Original Collection product list. <http://www.kahrs.com>

9. Wood Species, Design, and Finish [WF-#]: <insert product description from web site>.

2.2 UNDERLAYMENTS

- B. For floating and radiant heat installations:
 - 1. Kahrs Combo-System Foam Underlayment.
 - 2. Use of this product is required by warranty.
- C. Kahrs QuietStride underlayment plus vapor retarder complying with ASTM D 4397, polyethylene sheet not less than 6.0 mils (0.15 mm) thick. Kahrs approved moisture sealer may be substituted for 6.0 mil polyethylene sheet for QuietStride installations.
- D. For radiant heat floating installations: Kahrs Combo-System Foam Underlayment or Kahrs QuietStride underlayment plus vapor retarder complying with ASTM D 4397, polyethylene sheet not less than 6.0 mils (0.15 mm) thick. Kahrs approved moisture sealer may be substituted for 6.0 mil polyethylene sheet for QuietStride installations.

3.2 ACCESSORY MATERIALS

- E. Wood Flooring Adhesive: Mastic recommended by flooring and adhesive manufacturers for application indicated.
- F. Wood Trim: In same species and grade as wood flooring, unless otherwise indicated.
 - 1. Wood Base: Manufacturer's standard.
 - 2. Quarter Round Molding: Manufacturer's standard.
 - 3. T- Molding: Manufacturer's standard.
 - 4. Threshold: Tapered on each side and routed at bottom of one side to accommodate wood flooring.
 - 5. Reducer Strip: Manufacturer's standard.
 - 6. Square Nose Reducer Strip: Manufacturer's standard.
 - 7. Trim Fasteners: As recommended by manufacturer.
- G. Cleaning Agent: Kahrs Wood Floor Cleaner.