

## **DECLARATION OF CONTENTS**

Floor surface material, wood floor

**Supplier:** AB Gustaf Kähr

**Date:** 2009-04-01

**Product:** 10mm lacquered, three-layer wood floor, Spirit

<b>Components</b>	<b>Specifications</b>	<b>% by weight</b>	<b>g/m2</b>
Surface treatment	Acryl-based lacquer, UV cured	<1	<80
Wear layer	Chemically untreated species of wood in the product range. Thickness 1.9 mm	15	1440
Intermediate material	HPD sheet, 16% melamine glue (MUF) 84% pine fibers	78	6770
Base material	Chemically untreated veneer. Thickness 0,6 mm.	3	200
Glue	Urea-formaldehyde resin	< 3	220
Other components	Filler, hardened	< 0,4	< 2
	Summa	100	

### **Other information**

1. The information on percentage by weight and g/m2 are averages since the density varies both within and between species of wood.
2. The surface treatment and filler material are free from solvents and formaldehyde.
3. Urea-formaldehyde resin has water as a solvent.

### **Comments**

1. The declaration of contents state all the components included (newly-manufactured products) Summary designations can be used.
2. The proportions of the components are rounded off to the nearest percentage by weight and g/m2.
3. The values can be stated as a range.
4. Percentage proportions below 2% can be stated as <2% and the respective corresponding surface weight.