

Kährs

QUALITY IN WOOD SINCE 1857

TECHNICAL SPECIFICATION

KÄHRS LINNEA

INSTALLATION HEIGHT ¼" (7 MM)

Kährs International
940 Centre Circle | Suite 1000
Altamonte Springs | Florida | 32714
Phone: 1 800 800 5247 | Fax: 407 260 9933
Email: info@kahrs.com

Areas of application and special characteristics

Kährs Linnea is designed for residential applications. Linnea combines an attractive appearance with simple installation and a thin installation height.

- Real wood surface.
- Dimensionally stable due to climate-controlled production and balance between the upper and lower layers.
- HDF middle layer creates one of the hardest floors in Kährs range.
- Adds only 7 mm height to floor.
- Easy to install because of precision manufacturing and the Kährs Woodloc® joint.
- Available in more than 30 patterns and species to suit every taste.
- Natural and unique look.
- Pre-finished with UV-cured finish. Narrow products (except Hard Maple) are micro-beveled on all edges.
- Durable and easy to care for.
- Surface can be recoated.

Construction

- Three-layer boards with Kährs Woodloc® on all edges.
- High-grade veneer surface layer.
- Fiberboard (HDF) middle layer.
- Wood veneer bottom layer.

Thickness of surface layer

- 0.6 mm.

Surface treatment

- Pre-finished (for dry areas subject to normal wear), with UV-cured polyurethane/acrylic-based finish (satin approx. 30° Gardner, matte finish approx. 10° Gardner). The finish is free from solvents and formaldehyde. It is durable and preserves the wood's natural character.

Requirements for the subfloor

The subfloor must be firm, flat, and free from moisture and debris. Please see detailed subfloor requirements and preparation procedures in the Kährs Professional Installation Guides that are available for download from our web site at www.kahrs.com (Download Library).

Maintenance

Detailed information about maintenance is described in our Floor Care Guide and Guarantee. Download it from our web site at www.kahrs.com (Download Library).

Moisture content

Moisture content when delivered: 7%.

Weight per carton

- 24 lbs for 1-strip.
- 43 lbs for 2-, 3-strip.

Packaging

- Protective corrugated cardboard edging (100% recycled paper).
- Protective PE sheeting (recycled).

Pack contents

1-strip 18.72 sft/carton 48 ¼ inches long 4 5/8 inches wide
2-, 3-strip 30.569 sft/carton 48 ¼ inches long 7 5/8 inches wide