Test No: 292645



P.O. Box 1948

1503 Murray Ave.

Dalton, Georgia 30722-1948 • Phone 706-278-3013 • Fax 706-272-7057 • E-mail: info@ittslab.com

TEST REPORT

Customer: Dura Undercushions Ltd

September 2, 2009

Subject: Sample(s) were submitted for testing by the customer and identified below:

Sample Identification: Duracushion 6mm

Test Method Conducted Cushion Analysis

Test Method Conducted	Test Result		
Compression Set @ 50%	11.4%		
Compression Resistance @ 25%	5.2 psi		
Ash Content	41.8%		

L. Kent Suddeth

Executive Vice President

Test Number: 292645



P.O. Box 1948

1503 Murray Ave.

Dalton, Georgia 30722-1948 • Phone 706-278-3013 • Fax 706-272-7057 • E-mail: info@ittslab.com

TEST REPORT

Customer: Dura Undercushions Ltd

September 2, 2009

Subject:

"Consumer Product Safety Commission (CPSC) FF 1-70"

"16 CFR 1630" "ASTM D 2859-06"

Scope: This test method covers the determination of the flammability of finished textile floor covering materials when exposed to an ignition source under controlled laboratory conditions. It is applicable to all types of textile floor coverings regardless of the method of fabrication or whether they are made from natural or man-made fibers.

FLAMMABILITY TEST

STYLE	COLOR	ROLL	TESTED	PASSED
Duracushion 6mm			8	8

APPROVED MEETS OR EXCEEDS FEDERAL FLAMMABILITY STANDARD CPSC FF 1-70

L. Kent Suddeth

Executive Vice President