

# TECHNICAL DATA


## ESTRAD SOUND

### PRODUCT












Estrad Sound	EN 651	Sheet vinyl flooring with impact sound insulation
Application	EN ISO 10874	23/34/42



### SPECIFICATION

Thickness	 EN ISO 24346	3.7 mm
Weight	 EN ISO 23997	2550 g/m <sup>2</sup>
Wear layer	 EN ISO 24340	0.65 mm
Roll length	 EN ISO 24341	20 m
Width	 EN ISO 24341	2 m

### PRODUCT PROPERTIES

PROPERTY	TEST METHOD	RESULT
Indoor air certifications		M1, Floorscore
Fire resistance	 EN 13501-1	B <sub>fl</sub> -s1
Residual indentation	 EN ISO 24343-1	< 0.2 mm
Dimensional stability	 EN ISO 23999	< 0.1 %
Colour fastness	 EN ISO 105-B02	≥ 6 (Method 3)
Slip resistance	 EN 13893 DIN 51130	DS R10
Electrical propensity	 EN 1815	≤ 2 kV (antistatic)
Wear and scratch resistance	 EN 651	Class T
Chemical resistance	 EN 423	Excellent
Effect of castor chair	 EN 425/EN ISO 4918	Suitable
Underfloor heating	 ISO 8302	0.0525 m <sup>2</sup> K/W Suitable (max +27 °C)
Acoustic impact sound reduction	 EN ISO 10140-3 (EN ISO 140-8) ISO 717-2	≥ 19 dB ≥ 19 dB



# COLLECTION COLOURS ESTRAD SOUND



15502



15504



15509



15511



15512




15542



15544




15508



15529



15534



15559




15564



15505



15507



15503



15506



15543



15552



15545



15558



15548



15546