

TECHNICAL DATA

ZERO SOUND

ENOMER® CONTRACT SHEET FLOORING

PRODUCT

Zero Sound	EN 14565	PVC- and plasticizer free Enomer® flooring with additional acoustic qualities
Application	EN ISO 10874	23/34/42
		

SPECIFICATION

Thickness		EN ISO 24346	3.6 mm
Weight		EN ISO 23997	3800 g/m ²
Roll length		EN ISO 24341	8 - 16 m
Width		EN ISO 24341	145 cm

PRODUCT PROPERTIES


PROPERTY	TEST METHOD	RESULT
Indoor air certifications		M1, Floorscore
Fire resistance	 EN 13501-1	C _{fi} -s1
Residual indentation	 EN ISO 24343-1 (2.5 h)	approx. 0.13 mm
Slip resistance	 EN 13893 DIN 51130	DS (> 0.3) R9
Electrical propensity	 EN 1815	≤ 2 kV (antistatic)
Chemical Resistance	 EN ISO 26987	Excellent
Underfloor heating		Suitable (max. +28 °C)
Insulation resistance	 EN 1081	> 100 GΩ
Thermal resistance	 EN 12667	R = 0.030 [m ² K/W]
Impact sound reduction	 ISO 717-2	ΔL _w ~ 16 dB
Resistance to bacteria and fungi	ISO 846	Good




TECHNICAL DATA

ZERO SOUND


ENOMER® CONTRACT SHEET FLOORING




5803 PEWTER
NCS S 4500-N
LRV 28.8



5802 CAPE COD
NCS S 2500-N
LRV 49.8




5811 SILVER GREY
NCS S 3000-N
LRV 46.1




5805 GRAPHITE
NCS S 7500-N
LRV 10.2




5822 DUSTY
NCS S 2005-Y30R
LRV 48.3




5823 MOROCCO
NCS S 4010-Y30R
LRV 35.1




5824 CORUNDUM
NCS S 6005-Y50R
LRV 17.6




5829 SUNBEAM
NCS S 2030-Y20R
LRV 46.2




5832 CAROTENE
NCS S 2060-Y40R
LRV 30.4




5843 TERRACOTTA
NCS S 2060-Y80R
LRV 21.0




5852 BLUE MOON
NCS S 5020-R80B
LRV 15.9




5858 BLUE ORCHID
NCS S 4020-R90B
LRV 22.4



5859 DENIM
NCS S 6020-B
LRV 14.3



5868 PINE
NCS S 5010-G30Y
LRV 23.1



5864 AMBROSIA
NCS S 2005-G30Y
LRV 49.7