DECLARATION OF PERFORMANCE			
1.	Unique identification code of the product-type:		
	Estrad Safety R10/36+, Estrad Safety R11/45+, Estrad Safety R11/50+, Estrad Safety R12/45+		
2.	Type, batch or serial number or any other element allowing identification of the construction product as required pursuant to Article 11(4):		
	7740 - 7766		
3.	Intended use or uses of the construction product, in accordance with the applicable harmonised technical specifi- cation, as foreseen by the manufacturer:		
	For use as floor covering in buildings (see EN 14041) according to the manufacturer's specifications.		
4.	Name, registered trade name or registered trade mark and contact address of the manufacturer as required pursuant to Article 11(5):		
	Kährs Oy, Neulaniementie 2, 70210 Kuopio, Finland		
5.	Where applicable, name and contact address of the authorised representative whose mandate covers the tasks specified in Article 12(2):		
6.	System or systems of assessment and verification of constancy of performance of the construction product as set out in Annex V:		
	System 3		
7.	In case of the declaration of performance concerning a construction product covered by a harmonised standard: Name of the notified test laboratory, that has issued the certificate of conformity of the factory production control, inspection reports and calculation reports (if relevant).		
	British Textile Technology Group (BTTG) Wira House, West Park Road, Leeds, LS16 6QL.		not applicable
	Notified Body		certificate of constancy of performance
9.	not applicable Declared performance		
	Essential characteristics	Performance	Harmonised technical specification
	Reaction to fire	B _{ff} -s1	EN 14041: 2004/AC:2006
	Content of Pentachlorophenol	° DL PCP	EN 14041: 2004/AC:2006
	Formaldehyd Emissions	° NA HCHO	EN 14041: 2004/AC:2006
	Slip resistance	DS -	EN 14041: 2004/AC:2006
	Electrical behavior (dissipative)	NPD	EN 14041: 2004/AC:2006
	Electrical behavior (conductive)	NPD	EN 14041: 2004/AC:2006
	Electrical behavior (antistatic)	NPD	EN 14041: 2004/AC:2006
	Thermal conductivity [W/mK]	0,25 W/mK	EN 14041: 2004/AC:2006
	Water-tightness	NPD	EN 14041: 2004/AC:2006
10.	The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 9. This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4 Signed for and on behalf of the manufacturer by:		
	Tomi Tehomaa, Technical Product Manager, Kährs Oy (name and function) Kangasala 27.7.2022		

(place and date of issue)