



OAK EARTH

The smoked finish on this single-strip oak floor from the Artisan Collection enhances the natural colour variations for a rustic expression. Knots and cracks pepper the boards, adding depth and balancing the toasted sesame seed highlights. Each board is carefully brushed to bring out the character of the grain and highlight the natural texture of the wood. Four-sided bevelling at the edges ensures a classic full plank look and feel. Hand-scraping enhances the worn appearance of the floor.

PRODUCT DETAILS

Article Number / EAN-code	151YCDEKFCKW195 / 7393969305860
Product type / Construction	Wood Floors / 3-layer parquet
Design / Wood species	Plank / Oak
Surface Treatment / Natural/Stained	Oil / Natural
Features	Bevelled 4-sided, Smoked, Handscraped, Brushed
Width x Length x Thickness	190 mm x 1900 mm x 15 mm
Weight per package / Weight per m² (kg)	17 kg / 7.83 kg
Area per Package (m²) / Area per pallet (m²)	2.17 m² / 75.95 m²
Grading	Dynamic
Joint	Woodloc® 5G
Installation method	Glue-down, Floating
Floor heating	Yes
Wear-layer material / Wear Layer Thickness approx. (mm)	Hardwood / 3.5 mm
Resandable	2-3 times

PRODUCT DETAILS

Core material	Pine/Spruce
Backside material	Veneer
Brinell value / Brinell Range	3,7 / 2.2 - 5.9
Warranty	30 years
Collection	Artisan Collection
Joint	Woodloc® 5G

TECHNICAL PROPERTIES

Moisture content	EN13183	7%±2%
Minimun Mean Density kg/m³		>500 kg/m³
Reaction To Fire	EN13501-1	Dfl-s1
Formaldehyde Emission	EN717-1	E1
Content PCP	CEN/TR14823	≤ 5 x 10-6n
Breaking Strength N/mm²	EN1533	NPD
Biological Durability	EN350-2	Class 1
CARB2		Compliant
Thermal Conductivity	EN12664	0,11W/mK
Slip resistance	CEN/TS15676	NPD

DETAILED DESCRIPTION

All naturally occurring wood colour variations allowed, from light to dark brown. Sapwood may occur. The product includes very large sound and black knots and cracks. Partly filled knots and cracks will be present in all sizes and numbers. Any flaking in

Colour Change: The smoked finish accentuates the natural colour variations, creating a stronger contrast between light and dark tones initially. Over time, the colour variations will soften, resulting in a more uniform overall appearance. The oiled surface will develop

Oil: This floor should be oiled immediately after installation

Descriptions & Imagery: All samples, images and product description, plus photo and brochure specifications are therefor the sole purpose of giving an approximate idea of the items described in them.They shall not form part of the contract or have any contractual force and should be viewed for illustrative purposes only. We cannot guarantee that your computer's display or the quality of the print will accurately reflect the colour of the products.Your product may vary slightly from the images within this literature.

OTHER PRODUCTS IN THIS COLLECTION



MAPLE CAROB



OAK LINEN



OAK OYSTER



OAK STRAW



OAK BUCKSKIN



OAK EARTH



OAK CONCRETE



OAK CAMINO